

# Supermicro SuperServer SYS-F618R2-RTPT+ 4U FatTwin^4 DP 8x6SFF RED PSU

## Kod producenta: SYS-F618R2-RTPT+

Chassis Form Factor	Rack 4U
# of systems (nodes)	8
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets (per node)	2
Supported CPU's	Intel Xeon E5-2600v3
Max CPU TDP	145 W
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2133 MHz 1866 MHz 1600 MHz
# of DIMM's (per node)	16
Max Memory Size (per node)	1024 GB
Integrated GPU	Aspeed AST2400
# of 2.5 hot-swap bays (per node)	6
Backplanes	SAS2/SATA3
# of PCIe x16 3.0 (per node)	1
# of PCIe x8 3.0 (per node)	1
# of USB Ports (per node)	2 x USB 3.0 (rear)
# of SATA Ports (per node)	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports (per node)	1 x Fast UART 16550 (header)
# of 10GbE Ports (per node)	2 x RJ45
Network Controllers	Intel x540 Dual Port 10 Gigabit Base-T
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Power Supply	Redundant
PSU Wattage	1620W
PSU Certification	80+ Platinum
Chassis Dimensions	448 x 177 x 737mm
Uwagi	PCI-Express Slots Configuration: 1x PCI-E 3.0 x16 Low-profile 1xMicro Low Profile PCI-E 3.0 x8 slot MicroLP Adapter Matrix

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-f618r2-rtpt-4u-fattwin4-dp-8x6sff-red-psu-p-1025.html>