

Supermicro MBD-X10DRD-LT, Dual SKT, Intel C612 Chipset, SATA, 2x10GbE, IPMI

Kod producenta: MBD-X10DRD-LT-O



Form Factor	E-ATX
Dimensions	13" x 10.5"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	2
Supported CPU's	Intel Xeon E5-2600v3 Intel Xeon E5-2600v4
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	8
Max Memory Size	1024 GB
Integrated GPU	Aspeed AST2400
# of PCIe x8 3.0	1
# of USB Ports	4 x USB 2.0 (rear) 2 x USB 2.0 (header) 1 x USB 2.0 Type A
# of SATA Ports	6
# of SATA DOM power	2
Storage Controllers	6 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 10GbE Ports	2 x Base-T
Network Controllers	Intel x540 Dual Port 10 Gigabit Base-T
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header

Product SKUs		Chassis (Optimized for X10DRD-LT)	
MBD-X10DRD-LT -O			• SC514-441 • SC514-R400C • SC514-505 • SC813LT-350CB • SC813LT-R500CB
Physical Stats		1U Chassis:	
Form Factor	• E-ATX	Important Chassis Notes	Intel® Xeon® processor-based motherboards, Revision M chassis is recommended. Please talk to your sales representative for details.
Dimensions	• 13.05" x 10.5" (33.1cm x 26.7cm)		
Processor/Cache			
CPU	• Intel® Xeon® processor E5-2600 v4/v3 family (up to 145W TDP**) • Dual Socket R3 (LGA 2011)	Expansion Slots	
Cores / Cache	• Up to 22 Cores [†] / Up to 55MB [†] Cache	PCI-Express	• 1x PCI-E 3.0 x8 slot
System Bus	• QPI up to 9.6 GT/s	System BIOS	
Note	[†] BIOS version 2.0 or above is required	BIOS Type	• 128Mb SPI Flash EEPROM with AMI BIOS • Plug and Play (PnP) • PCI 2.3 • ACPI 1.0 / 2.0 / 3.0 / 4.0
Note	** Motherboard supports this maximum TDP. Please verify your system can thermally support.	BIOS Features	• USB Keyboard support • SMBIOS 2.7.1 • UEFI 2.3.1
System Memory		Management	
Memory Capacity	• 8x 288-pin DDR4 DIMM slots • Up to 1TB[†] ECC 3DS LRDIMM, 256GB ECC RDIMM	Software	• Intel Node Manager • IPMI 2.0 • NMI • SuperDoctor® 5 • Watch Dog
Memory Type	• 2400 /2133/1866/1600MHz ECC DDR4 SDRAM 72-bit	Power Configurations	• ACPI Power Management • Power-on mode for AC power recovery
DIMM Sizes	• RDIMM: 32GB, 16GB, 8GB, 4GB • LRDIMM: 64GB, 32GB • 3DS LRDIMM: 128GB	PC Health Monitoring	
Memory Voltage	• 1.2 V	Voltage	• Monitors for CPU Cores, +3.3V, +5V, +12V, +5V Standby, +3.3V Standby, VBAT, Memory Voltages. • 4 Phase-switching voltage regulator
Error Detection	• Corrects single-bit errors	FAN	• 8x 4-pin fan headers (up to 8 fans) • 8x fans with tachometer monitoring • Status monitor for speed control • Pulse Width Modulated (PWM) fan connectors
On-Board Devices		Temperature	• Monitoring for CPU and chassis environment • CPU thermal trip support • Thermal Control for 8x Fan Connectors • Thermal Monitor 2 (TM2) support • PECI
Chipset	• Intel® C612 chipset	LED	• CPU / System Overheat LED • Suspend static indicator LED • UID/Remote UID
AHCI SATA	• SATA3 (6Gbps); RAID 0, 1, 5, 10 • Support for Intelligent Platform Management Interface v.2.0	Other Features	• RoHS
IPMI	• IPMI 2.0 with virtual media over LAN and KVM-over-LAN support • ASPEED AST2400 BMC • Intel® X540 Dual Port 10GBase-T • Virtual Machine Device Queues reduce I/O overhead	Operating Environment	
Network Controllers	• Supports 10GBase-T, 100BASE-TX, and 1000BASE-T, RJ45 output • 1x Realtek RTL8211E PHY (dedicated IPMI)	Operating Temperature Range	
Video	• ASPEED AST2400 BMC	Non-Operating Temperature Range	
Input / Output		Operating Relative Humidity Range	
SATA	• 6x SATA3 (6Gbps) ports	Non-Operating Relative Humidity Range	
LAN	• 2x RJ45 10GBase-T ports • 1x RJ45 Dedicated IPMI LAN port		
USB	• 7x USB 2.0 ports total (4 rear, 2 via headers, 1 Type A)		
Video	• 1x VGA port		
Serial Port / Header	• 2x COM Ports (1 rear, 1 header)		
DOM	• 2x Super DOM (Disk on Module) ports		
TPM	• 1x TPM Header		

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-mbd-x10drd-lt-dual-skt-intel-c612-chipset-sata-2x10gbe-ipmi-p-1343.html>