

# Supermicro SuperServer SYS-6027R-72RFT 2U DP 8xLFF 2x10Gb RED PSU

**Kod producenta: SYS-6027R-72RFT**



*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

Product SKUs <input type="checkbox"/>	SYS-6027R-72RFT • SuperServer 6027R-72RFT (Black)	<input type="checkbox"/>	Chassis <input type="checkbox"/>
Motherboard <input type="checkbox"/>	<b>Super X9DRH-7TF</b>	<input type="checkbox"/>	Form Factor • 2U Rackmount Model • <b>CSE-825TO-R740LPB</b>
Processor/Cache <input type="checkbox"/>	CPU • Dual Socket R (LGA 2011) • Intel® Xeon® processor E5-2600 and E5-2600 v2 family' Note † BIOS version 3.0 or above is required Cache • Up to 30MB System Bus • QPI up to 8 GT/s	<input type="checkbox"/>	Dimensions <input type="checkbox"/>
System Memory <input type="checkbox"/>	Memory Capacity • 16x 240-pin DDR3 DIMM slots • Up to 1TB DDR3 ECC LRDIMM • Up to 512GB DDR3 ECC Registered memory (RDIMM) • Up to 128GB DDR3 ECC Un-Buffered memory (UDIMM) Memory Type • 1866/1600/1333/1066/800MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs DIMM Sizes • 32GB, 16GB, 8GB, 4GB, 2GB, 1GB Memory Voltage • 1.5 V, 1.35 V Error Detection • Corrects single-bit errors • Detects double-bit errors (using ECC memory)	<input type="checkbox"/>	Width • 17.2" (437mm) Height • 3.5" (89mm) Depth • 25.5" (648mm) Gross Weight • 52 lbs (23.6kg) Available Colors • Black
On-Board Devices <input type="checkbox"/>	Chipset • Intel® C602 Chipset • Via Cable for SATA controller SATA • SATA 2.0 3Gbps with RAID 0, 1, 5, 10 • SATA 3.0 6Gbps with RAID 0, 1, 5, 10 SAS • SAS2 from LSI 2208 • HW RAID 0, 1, 5, 6, 10, 50, 60 support • Support for Intelligent Platform Management Interface v.2.0 IPMI • IPMI 2.0 with virtual media over LAN and KVM-over-LAN support • Nuvoton WPCM450 BMC • Intel® X540 Dual Port 10GBase-T • Virtual Machine Device Queues reduce I/O overhead • Supports 10GBase-T, 100BASE-TX and 1000BASE-T, RJ45 output • 1x Realtek RTL8201N PHY (dedicated IPMI) Network Controllers • Matrox G200eW Graphics	<input type="checkbox"/>	Front Panel <input type="checkbox"/>
Input / Output <input type="checkbox"/>	Serial ATA • 2x SATA 3.0 ports (6Gbps) • 8x SATA 2.0 ports (3Gbps) SAS • 8x SAS2 ports (6Gbps) LAN • 2x RJ45 10GBase-T ports • 1x RJ45 Dedicated IPMI LAN port USB • 2x Front USB 2.0 + 4x Rear USB 2.0 ports • MB: 4x rear + 2x via header + 1x Type A VGA • 1x VGA port Serial Port / Header • 2x Fast UART 16550 ports	<input type="checkbox"/>	Buttons • Power On/Off button • System Reset button • Power status LED • Hard drive activity LED LEDs • 2x Network activity LEDs • System Overheat LED • Power fail LED
		<input type="checkbox"/>	Expansion Slots <input type="checkbox"/>
		<input type="checkbox"/>	PCI-Express • 1 PCI-E 3.0 x16 slot • 6 PCI-E 3.0 x8 slots
		<input type="checkbox"/>	Drive Bays <input type="checkbox"/>
		<input type="checkbox"/>	Hot-swap • 8x 3.5" Hot-swap SAS2/SATA HDD trays
		<input type="checkbox"/>	Peripheral Drives <input type="checkbox"/>
		<input type="checkbox"/>	DVD-ROM • Slim DVD-ROM drive (optional)
		<input type="checkbox"/>	Backplane <input type="checkbox"/>
		<input type="checkbox"/>	1x SAS2 / SATA backplane
		<input type="checkbox"/>	System Cooling <input type="checkbox"/>
		<input type="checkbox"/>	Fans • 3x 8cm 7k RPM middle fans
		<input type="checkbox"/>	Power Supply with Power Distributor <input type="checkbox"/>
		<input type="checkbox"/>	740W (1+1) Redundant high-efficiency power supply with PMBus
		<input type="checkbox"/>	AC Input • 100-240 V, 50-60 Hz, 9-3.5 Amp
		<input type="checkbox"/>	DC Output • 4 Amp @ +5V standby • 61.7 Amp @ +12V • +5V: 30 Amp With Power • +3.3V: 24 Amp Distributor • -12V: 0.6 Amp
		<input type="checkbox"/>	Certification <b>Platinum Certified</b> <b>[ Test Report ]</b>
		<input type="checkbox"/>	System BIOS <input type="checkbox"/>
		<input type="checkbox"/>	BIOS Type • 128Mb SPI Flash EEPROM with AMI BIOS • Plug and Play (PnP) • APM 1.2 • PCI 2.2 BIOS Features • ACPI 1.0 / 2.0 • USB Keyboard support • SMBIOS 2.3 • UEFI
		<input type="checkbox"/>	Operating Environment / Compliance <input type="checkbox"/>
		<input type="checkbox"/>	RoHS • RoHS Compliant • Operating Temperature: 10°C to 35°C (50°F to 95°F) • Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Environmental Spec. • Operating Relative Humidity: 8% to 90% (non-condensing) • Non-operating Relative Humidity: 5% to 95% (non-condensing)

## UWAGA !!!

*Oferowany produkt to platforma serwerowa służąca do budowy swojej własnej konfiguracji serwera (nie zawiera CPU, RAM czy HDD).*

*Jeżeli potrzebujesz kupić gotowy serwer wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas serwerów.*

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-6027r-72rft-2u-dp-8x16-2x10gb-red-psu-p-1952.html>

