

Supermicro SuperServer SYS-F618R2-FT+ 4U FatTwin^4 DP 8x2SFF RED PSU

Kod producenta: SYS-F618R2-FT+

Chassis Form Factor	Rack 4U
# of systems (nodes)	8
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets (per node)	2
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3
Max CPU TDP	145 W
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's (per node)	16
Max Memory Size (per node)	2048 GB
Integrated GPU	Aspeed AST2400
# of 2.5 fixed bays (per node)	4
# of PCIe x8 3.0 (per node)	1
# of PCIe x4 2.0	1
# of USB Ports (per node)	2 x USB 3.0 (rear)
# of SATA Ports (per node)	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports (per node)	1 x Fast UART 16550 (header)
# of 1GbE Ports (per node)	2 x RJ45
Network Controllers	Intel i350 Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Power Supply	Redundant
PSU Wattage	2000W
PSU Certification	80+ Titanium
Chassis Dimensions	448 x 177 x 737mm
Uwagi	PCI-Express Slots Configuration: 1x PCI-E 3.0 x8 slot 1x PCI-E 2.0 x4 slot 2x PCI-E 3.0 x8 slots (optional)



Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

SYS-F618R2-FT+ • SuperServer F618R2-FT+ (Black)

Motherboard

Super X10DRFF-IG

Processor/Cache

CPU • Intel® Xeon® processor E5-2600 v4†/ v3 family (up to 145W TDP) *
• Dual Socket R3 (LGA 2011)
Cores / Cache • Up to 22 Cores† / Up to 55MB† Cache
System Bus • QPI up to 9.6 GT/s
Note † BIOS version 2.0 or above is required
* Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

System Memory

Memory Capacity • 16x 288-pin DDR4 DIMM slots
• Up to 2TB† ECC 3DS LRDIMM, 1TB ECC RDIMM
Memory Type • 2400†/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit
• RDIMM: 64GB, 32GB, 16GB, 8GB, 4GB
DIMM Sizes • LRDIMM: 64GB, 32GB
• 3DS LRDIMM: 128GB
Memory Voltage • 1.2 V
Error Detection • Corrects single-bit errors

On-Board Devices

Chipset • Intel® C612 chipset
SATA • SATA3 (6Gbps) with RAID 0, 1, 5, 10
• Support for Intelligent Platform Management Interface v.2.0
IPMI • IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
• ASPEED AST2400 BMC
• Intel® i350 Dual Port Gigabit Ethernet
• Virtual Machine Device Queues reduce I/O overhead
Network Controllers • Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output
• 1x Realtek RTL8211E PHY (dedicated IPMI)
Graphics • ASPEED AST2400 BMC

Input / Output (per node)

SATA • 10x SATA3 (6Gbps) ports
LAN • 2x RJ45 Gigabit Ethernet LAN ports
• 1x RJ45 Dedicated IPMI LAN port
USB • 2x USB 3.0 ports
VGA • 1x VGA port

Chassis

Form Factor • 4U Rackmount
Model • CSE-F4181F2-R2K04B

Dimensions and Weight

Width • 17.63" (448mm)
Height • 6.96" (177mm)
Depth • 29" (737mm)
Package • 28.35" (W) x 14.95" (H) x 42.38" (D)
Weight • Net Weight: 150 lbs (68.04 kg)
• Gross Weight: 200 lbs (90.72 kg)
Available Colors • Black

Front Panel

Buttons • Power On/Off button
• UID button
LEDs • Power status LED
• 2x Network activity LEDs

Expansion Slots (per node)

PCI-Express • 1x PCI-E 3.0 x8, 1x PCI-E 2.0 x4, or 2x PCI-E 3.0 x8 (optional)

Drive Bays (per node)

Fixed • 4x 2.5" fixed drives

System Cooling

Fans • 8x 8cm 9.5k RPM Rear fans

Power Supply with Digital Switching Control
2000W Titanium Level (96%) High-efficiency Redundant Power Supplies

Total Output Power • 1000W/1800W/1980W/2000W

AC Input • 100-127 V, 50-60 Hz
• 200-220 V, 50-60 Hz
• 220-230 V, 50-60 Hz
• 230-240 V, 50-60 Hz
• Max: 83.3A & Min: 0A (100Vac-127Vac)
• Max: 150A & Min: 0A (200Vac-220Vac)
• Max: 165A & Min: 0A (220Vac-230Vac)
• Max: 166.7A & Min: 0A (230Vac-240Vac)
+12V • Max: 1A / Min: 0A
5V SB • Max: 1A / Min: 0A

Certification Titanium Level [Test Report]

System BIOS

BIOS Type • 128Mb SPI Flash EEPROM with AMI BIOS
• Plug and Play (PnP)
• APM 1.2
• PCI 2.3
BIOS Features • ACPI 1.0 / 2.0 / 3.0 / 4.0
• USB Keyboard support
• SMBIOS 2.7.1
• UEFI 2.3.1

Operating Environment / Compliance

RoHS • RoHS Compliant
• Operating Temperature: 10°C to 35°C (50°F to 95°F)
• Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
Environmental Spec. • Operating Relative Humidity: 8% to 90% (non-condensing)
• Non-operating Relative Humidity: 5% to 95% (non-condensing)

UWAGA !!!

Oferowany produkt to platforma serwerowa służąca do budowy swojej własnej konfiguracji serwera (nie zawiera CPU, RAM czy HDD).

Jeżeli potrzebujesz kupić gotowy serwer wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas serwerów.

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-f618r2-ft-4u-fattwin4-dp-8x2sff-red-psu-p-1972.html>