

Supermicro SuperChassis SC213A-R740WB 2U 16xSFF RED PSU

Kod producenta: CSE-213A-R740WB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	740W
PSU Certification	80+ Titanium



Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-213A-R740WB • SuperChassis 213A-R740WB (black)

Form Factor

2U chassis supports SMC Proprietary WIO motherboards;
max. motherboard size - 12" x 13", 13" x 13.68"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width • 17.2" (437mm)
Height • 3.5" (89mm)
Depth • 24.8" (630mm)
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)
Weight • Gross: 50 lbs (22.7kg) / Net: 46 lbs (20.9kg)
Available Color • Black

Expansion Slots

• 4x Full-height, Full-length and 3x Low-profile expansion slots

Drive Bays

Hot-swap 16x 2.5" SAS / SATA Hot-swap drive bays
SAS or enterprise SATA HDD only recommended

Peripheral Bay 1x 5.25" peripheral Drive Bay
1x Slim Optical Drive Bay
1x USB/COM Port Bay

Backplane

2U Direct Attached Backplane, features:
• 3Gb/6Gb support
• SES-2 Enclosure Management Support
• SAS/SATA support
• Four SFF 8087 connectors

Peripheral Drives

DVD-ROM 1x Slim DVD-ROM Drive, 2x USB + 1x COM port (option)

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
• Hard drive activity LED

LEDs • 2x Network activity LEDs
• System Information LED
• Power fail LED

Motherboard (for CSE-213A-R740WB)

[X10DDW-i](#) [X10DDW-iN](#)
[X10DRW-E](#) [X10DRW-ET](#)
[X10DRW-N](#) [X10DRW-NT](#)
[X10SRW-F](#) [X9DRW-3F](#)
[X9DRW-iF](#)

Server(s) for SC213A-R740WB

[2027R-WRF](#)

System Cooling

Fans 3x 80mm 7,000 RPM 4-pin PWM fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply with Power Distributor

740W (1+1) Redundant high-efficiency power supply with PMBus
AC Input • 100-240 V, 50-60 Hz, 9-3.5 Amp
DC Output • 4 Amp @ +5V standby
• 61.7 Amp @ +12V
• +5V: 45 Amp
With Power Distributor • +3.3V: 24 Amp
• -12V: 0.6 Amp

Certification



Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- CCC Certification

Strona firmowa produktu:

<https://www.superchassis.pl/sc213a-r740wb-2u-16-bay-2027r-wrf> su-p-2972.htm 2 / 3

