

Supermicro SuperChassis SC826BE16-R920LPB 2U 12xLFF RED PSU

Kod producenta: CSE-826BE16-R920LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-826BE16-R920LPB • SuperChassis 826BE16-R920LPB
(Black)

Form Factor

2U chassis support for max. motherboard size - 13.68" x 13" and E-ATX

*Support up to E-ATX 12"x13" MB with rear 2.5" HDD option installed

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width 17.2" (437mm)
Height 3.5" (89mm)
Depth 25.5" (648mm)
Gross Weight 52 lbs (23.6kg)
Packaging • 26.7" (W) x 11.4" (H) x 34.5" (L)
Available Colors Black

Expansion Slots

• 7x low-profile full-length expansion slots

Drive Bays

Hot-swap 12x 3.5" SAS / SATA Hot-swap drive trays and optional 2x 2.5" Hot-swap SAS/SATA Drive Bays on rear side of Chassis
*SAS or enterprise SATA HDD only recommended

Backplane

2U Expander Backplane, features:

- Up to 6Gb support
- SES-2 Enclosure Management Support
- SAS/SATA support
- Two SFF 8087 connectors

Front Panel

Buttons • Power On/Off button
• System Reset button

Motherboard (for CSE-826BE16-R920LPB)

[H8DG6](#) [H8DG6-F](#)
[H8DGi](#) [H8DGi-F](#)
[X9DB3-F](#) [X9DB3-TPF](#)
[X9DBi-F](#) [X9DBi-TPF](#)
[X9DR3-F](#) [X9DR7-TF+](#)
[X9DRD-7LN4F](#) [X9DRD-7LN4F-JBOD](#)
[X9DRD-EF](#) [X9DRE-LN4F](#)
[X9DRE-TF+](#) [X9DRH-7F](#)
[X9DRH-7TF](#) [X9DRH-iF](#)
[X9DRH-iF-NV](#) [X9DRH-iTF](#)
[X9DRi-F](#)

System Cooling

Fans 3x 80mm 7K RPM Chassis middle fan w/ housing

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 10 - 35°C (50° - 95°F)
Range
Non-Operating Temperature • -40 - 60°C (-40° - 140°F)
Range
Humidity Range • 8 - 90% non-condensing
Non-Operating Humidity Range • 5 - 95% non-condensing

Power Supply with Power Distributor

920W high-efficiency (94+%) power supply with PMBus

AC Input • 100-240 V, 50-60 Hz, 11-4.4 Amp
DC Output • 4 Amp @ +5V standby
• 75 Amp @ +12V
With Power Distributor • +5V: 45 Amp
• +3.3V: 24 Amp
• -12V: 0.6 Amp

Certification



Platinum Certified

[\[Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed
• Canada - CUL listed
• Germany - TUV Certified
• EN 60950/IEC 60950-Compliant
• CB Report
• CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826be16-r920lpb-2u-12x1ff-red-psu-p-2185.html>