

Supermicro SuperChassis SC815TQ-600WB 1U 4xLFF FIX PSU

Kod producenta: CSE-815TQ-600WB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	600 W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 650mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-815TQ-600WB • SuperChassis 815TQ-600WB (Black)

Form Factor

1U chassis support for max. motherboard size - 13.68" x 13" E-ATX; optimized for WIO motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 1.7" (43mm)
Width • 17.2" (437mm)
Depth • 25.6" (650mm)
Gross Weight • 36 lbs (16.3kg)
Package • 23.5" x 8.5" x 33.7"
Available Colors • Black

Expansion Slots

- 2x Full-height PCI Expansion Slots (Riser Card Required)
- 1x Low-profile PCI Expansion Slot (Riser Card Required)

Drive Bays

- 4x 3.5" SAS / SATA Hot-swap drive trays
- Hot-swap • SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

DVD-ROM • Slim DVD-ROM drive (optional)

Front Panel

Buttons • Power On/Off Button
• System Reset Button
• UID Button
• Power LED
LEDs • Hard drive activity LED
• 2x Network activity LEDs
• System information (overheat/UID) LED
Ports • 2x USB & DB9 COM port tray
• (Optional - in place of floppy drive)

Motherboard (for CSE-815TQ-600WB)

[X10DDW-i](#) [X10DDW-iN](#)
[X10DRW-E](#) [X10DRW-ET](#)
[X10DRW-i](#) [X10DRW-iT](#)
[X10DRW-N](#) [X10DRW-NT](#)
[X10SRW-F](#) [X9DRD-CNT+](#)
[X9DRD-CT+](#) [X9DRD-iT+](#)
[X9DRW-3F](#) [X9DRW-iF](#)
[X9SRW-F](#) [X9SRW-F](#)

Server(s) for SC815TQ-600WB

[6017R-TDT+](#) [6017R-NTF](#)
[6018R-TDW](#)

System Cooling

Fans • 4x 4cm Counter-rotating PWM fans

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

600W High-Efficiency Power Supply w/PMBus 1.2, I²C, PFC, and Digital Switching
AC Input • 100-240V, 50-60Hz, 7.5A max
• +3.3V: 15A
• +5V: 18A
DC Output • +5V standby: 3A
• +12V: 49A
• -12V: 0.5A

Certification



Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply • China - CCC Mark
- Safety / EMC • Europe/CE Mark
- EN 60950/IEC 60950-Compliant
- Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc815tq-600wb-1u-4-bay-fixed-rpsu-p-2196.html> Strona: 2 / 3

