

Supermicro SuperChassis SC116AC-R700WB 1U 10xSFF RED PSU

Kod producenta: CSE-116AC-R700WB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	10
Power Supply	Redundant
PSU Wattage	750W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 597mm
Uwagi	SAS 3.0 12Gb/S Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-116AC-R700WB • SuperChassis 116AC-R700WB (Black)

Form Factor

- 1U chassis for motherboard support size of 12" x 13"
- Optimized for WIO (W series) motherboards

Processor Support

Supports dual Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 23.5" (597mm)
- Packaging • 25" (W) x 6" (H) x 33" (L)
- Gross Weight • 40 lbs (18.2 kg)
- Available Color • Black

Expansion Slots

Without Universal I/O (UIO) Card:

- 2x Full-height Expansion Slots (Riser Card Required)
- 1x Low-profile Expansion Slot (Riser Card Required)

Drive Bays

- 10x 2.5" hot-swap SAS/SATA drive bay
- Hot-swap SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane with SES2 BPN-SAS3-116A

Front Panel

- Buttons
 - Power On/Off button
 - Unit Identification (UID) button
- LEDs
 - Power status LED
 - HDD activity LED
 - 2x Network activity LEDs
 - Universal Information (UID) LED

Motherboard (for CSE-116AC-R700WB)

[X10SRW-F](#)
[X9DRW-CTF31](#)

[X9DRW-CF31](#)

Server(s) for SC116AC-R700WB

[1028R-WC1R](#)
[1027R-WC1RT](#)

[1027R-WC1R](#)

System Cooling

- Fans - 4x 40x56mm Counter-rotating PWM fans (Opt. 2x fans for AOC cooling)

Operating Environment (System)

- Operating Temperature Range - 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range - -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range - 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)

Power Supply

- 700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C
- AC Voltage
 - 700W: 100 - 140 V, 50-60 Hz, 8.5-6 Amp
 - 750W: 180 - 240V, 60-50 Hz, 5-3.8 Amp
- DC Output
 - +5V standby - 3 Amp
 - DC Output +12V
 - 700W: 58 Amp @ 100-140V
 - 750W: 62 Amp @ 180-240V
- With Power Distributor
 - +5V: 25 Amp
 - +3.3V: 12 Amp
 - -12V: 0.6 Amp

Certification



[Gold Certified](#)

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply Safety / EMC
 - CCC Certification
 - EN 60950/IEC 60950-Compliant
 - Europe/CE Mark

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc116ac-r700wb-1u-10xsff-red-psu-p-2198.html>