

Supermicro SuperChassis SC118G-1400B 1U 6xSFF FIX PSU

Kod producenta: CSE-118G-1400B



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	6
Power Supply	Fixed
PSU Wattage	1400W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 724mm
Uwagi	Ideal for High-end, high-density GPU Applications

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs (*OEM Only)

CSE-118G-1400B • SuperChassis 118G-1400B (Black)

Form Factor

1U Rackmount Chassis 28.5" depth, optimized for proprietary 16.64" x 7.71" motherboards and compatible with Twin motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 28.5" (724mm)
- Packaging • 24" (W) x 8" (H) x 36.3" (L)
- Gross Weight • 38 lbs (17.2 kg)
- Available Color • Black

Expansion Slots

Support up to 2 double width GPU with 1 Low-profile card or 2 Full-height, 1 Low-profile and 2 Full-height, Full-length AOC

Drive Bays

- Hot-swap • 6x 2.5" Hot-swap SAS/SATA drive bays
- SAS or enterprise SATA HDD only recommended

Backplane

1U SAS/SATA HDD Backplane

Front Panel

- Buttons • Power On/Off button
- System Reset button
- Power status LED
- Hard drive activity LED
- LEDs • 2x Network activity LEDs
- System Overheat LED

Motherboard (for CSE-118G-1400B)

[H8DGG-QF](#) [X8DTG-DF](#)

Server(s) for SC118G-1400B

- [6016XT-TF](#) [1026GT-TF-FM109](#)
- [1026GT-TF-FM275](#) [1026GT-TF](#)
- [1026GT-TF-FM107](#) [1026GT-TF-FM207](#)
- [1026GT-TRF-FM307](#) [1026GT-TRF-FM309](#)
- [1026GT-TRF-FM375](#) [1026GT-TRF](#)
- [6016GT-TF-FM109](#) [6016GT-TF-FM175](#)
- [6016GT-TF-FM209](#) [6016GT-TF-FM275](#)
- [6016GT-TF](#) [6016GT-TF-FM107](#)
- [6016GT-TF-FM207](#) [6016T-GIBXF](#)
- [6016T-GTF](#) [6016T-GIBQE](#)

System Cooling

- Fans • 2x 40x56mm fans for each double width GPU add on card; 4x 40x56mm fans for motherboard (8x fans total)

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

- 1400W high-efficiency power supply with PMBus
- 1200W: 100 - 140V, 50 - 60Hz, 10.5 - 14.7 Amp
- AC Input • 1400W: 180 - 240V, 50 - 60Hz, 7.2 - 9.5 Amp
- DC Output +5V standby • 4 Amp
- DC Output +12V • 100 Amp @ 100-140V
- 117 Amp @ 180-240V
- With Power Distributor • +5V: 14 Amp



Certification

Gold Certified
[[Test Report](#)]

Regulatory (Power Supply)

- Power Supply Safety / EMC • USA - UL listed, FCC
- Canada - CUL listed
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant
- Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc118g-1400b-1u-6xsff-fix-psu-p-2200.html>