

Supermicro SuperChassis SC113MTQ-330CB 1U 8xSFF FIX PSU

Kod producenta: CSE-113MTQ-330CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	330W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 508mm



Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-113MTQ-330CB • SuperChassis 113MTQ-330CB (Black)

Form Factor

19.98" Depth 1U Rackmount Chassis - support M-ATX (9.6" x 9.6") and ATX (12" x 10") motherboard (max MB size support: 13.68" x 10.5")

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 1.7" (43mm)
Width • 17.2" (437mm)
Depth • 19.98" (508mm)
Packaging • 24" (W) x 8.5" (H) x 30" (L)
Weight • Net Weight: 18.5 lbs (8.4kg)
• Gross Weight: 29.5 lbs (13.4kg)
Available Color • Black

Expansion Slots

• 1x Full-height AOC expansion slot

Drive Bays

Hot-swap • 8x Hot-swap 2.5" SAS/SATA HDD trays
SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane with SES2

Front Panel

Buttons • Power On/Off button
• System Reset button
• UID button
LEDs • Power status LED
• HDD activity LED
• 2x Network activity LEDs
• Universal Information (UID) LED

Motherboard (for CSE-113MTQ-330CB)

H8SCM	H8SCM-F
H8SGL	H8SGL-F
H8SML-7	H8SML-7F
H8SML-i	H8SML-iF
X10SL7-F	X10SLH-F
X10SLL+ -F	X10SLL-F
X10SLM+ -F	X10SLM+ -LN4F
X10SLM-F	X9SCL-LN4
X9SCL	X9SCL+ -F
X9SCL-F	X9SCM
X9SCM-F	X9SCM-iiF
X9SRH-7F	X9SRH-7TF
X9SRi	X9SRi-3F
X9SRi-F	

Server(s) for SC113MTQ-330CB

[1017R-MTF](#) [1018D-73MTF](#)

System Cooling

Fans • 3x 40x28mm high-efficiency PWM fans
(Optional 3x fans for AOC cooling)

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

330W AC power supply w/ PFC
AC Voltage • 100-240 V, 50-60 Hz, 4.5 Amp max
+5V • 18 Amp
+5V standby • 3 Amp
+12V • 27 Amp @ 100-180Vac,
31 Amp @ 180-240 Vac
-12V • 0.5 Amp
+3.3V • 15 Amp



Certification

Gold Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• EN 60950/IEC 60950-Compliant
• Europe/CE Mark
• Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113mtq-330cb-1u-8xsff-fix-psu-p-2212.html>