

Supermicro SuperChassis SC113TQ-R700CB 1U 8xSFF RED PSU

Kod producenta: CSE-113TQ-R700CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	700W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 597mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-113TQ-R700CB • SuperChassis 113TQ-R700CB (Black)

Form Factor

23.5" Depth 1U Rackmount Chassis - support for motherboard sizes of 12" x 13"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 1.7" (43mm)
Width • 17.2" (437mm)
Depth • 23.5" (597mm)
Packaging • 25" (W) x 6" (H) x 33" (L)
Gross Weight • 25 lbs (11.34kg)
Available Color • Black

Expansion Slots

• 1x Full-height & Full-length PCI expansion slot (riser card required)

Drive Bays

Hot-swap • 8x Hot-swap 2.5" SAS / SATA HDD tray SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane with SES2

Peripheral Drives

DVD-ROM • Slim DVD-ROM drive

Front Panel

Buttons • Power On/Off button
• System Reset button
• UID button
LEDs • Power status LED
• HDD activity LED
• 2x Network activity LEDs
• Universal Information (UID) LED

Motherboard (for CSE-113TQ-R700CB)

[X9DRD-7LN4F](#) [X9DRD-7LN4F-JBOD](#)
[X9DRD-EF](#)

Server(s) for SC113TQ-R700CB

[1027R-73DARE](#)

System Cooling

Fans • 4x 40x56mm Counter-rotating PWM fans
(Optional 2x fans for AOC cooling)

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C

AC Voltage • 700W: 100 - 140 V, 50-60 Hz, 8.5-6 Amp
• 750W: 180 - 240V, 60-50 Hz, 5-3.8 Amp

DC Output +5V standby • 3 Amp
DC Output +12V • 700W: 58 Amp @ 100-140V
• 750W: 62 Amp @ 180-240V
With Power Distributor • +5V: 25A
• +3.3V: 12A
• -12V: 0.6A

Certification



[Gold Certified](#)

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• CCC Certification
• EN 60950/IEC 60950-Compliant
• Europe/CE Mark
• Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113tq-r700cb-1u-8xsff-red-psu-p-2223.html>