

# Supermicro SuperChassis SC113TQ-R700UB 1U 8xSFF RED PSU

Kod producenta: CSE-113TQ-R700UB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	700W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 597mm



*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs (\*OEM Only)

CSE-113TQ-R700UB • SuperChassis  
113TQ-R700UB (Black)

## Form Factor

23.5" Depth 1U Rackmount Chassis

- Support E-ATX motherboard size 12" x 13"
- Optimized for Universal I/O (UIO) motherboard

## Processor Support

Supports dual Intel® / AMD processors

## Dimensions

Height • 1.7" (43mm)  
Width • 17.2" (437mm)  
Depth • 23.5" (597mm)  
Packaging • 25" (W) x 6" (H) x 33" (L)  
Gross Weight • 25 lbs (11.34kg)  
Available Color • Black

## Expansion Slots

• 1x Low-profile and 2x Full-height PCI expansion slots  
(riser card required)

## Drive Bays

Hot-swap • 8x Hot-swap 2.5" SAS / SATA HDD tray  
SAS or enterprise SATA HDD only recommended

## SAS / SATA Backplane

1x 1U SAS / SATA backplane with SES2

## Peripheral Drives

DVD-ROM • Slim DVD-ROM drive

## Front Panel

Buttons • Power On/Off button  
• System Reset button  
• UID button

LEDs • Power status LED  
• HDD activity LED  
• 2x Network activity LEDs  
• Universal Information (UID) LED

## Motherboard (for CSE-113TQ-R700UB )

[H8DGU](#)  
[X8DTU](#)

[H8DGU-F](#)

## System Cooling

Fans • 4x 40x56mm Counter-rotating PWM fans

## Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)  
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)  
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)  
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

## Power Supply

700W AC power supply w/ PFC (24-pin)

AC Voltage • 700W: 100 - 140 V, 50-60 Hz, 8.5-6 Amp  
• 750W: 180 - 240V, 60-50 Hz, 5-3.8 Amp

DC Output +5V standby • 3 Amp

DC Output +12V • 700W: 58 Amp @ 100-140V  
• 750W: 62 Amp @ 180-240V

With Power Distributor • +5V: 25 Amp  
• +3.3V: 12 Amp  
• -12V: 0.6 Amp

## Certification



[Gold Certified](#)

## Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC  
• Canada - CUL listed  
• CCC Certification  
• EN 60950/IEC 60950-Compliant  
• Europe/CE Mark  
• Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113tq-r700ub-1u-8xsff-red-psu-p-2224.html>