

Supermicro SuperChassis SC811TQ-441B 1U 2xLFF FIX PSU

Kod producenta: CSE-811TQ-441B



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	2
Power Supply	Fixed
PSU Wattage	440W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-811TQ-441B • SuperChassis 811TQ-441B (Black)

Form Factor

1U chassis support for max. motherboard size - 12" x 10" ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	• 1.7" (43mm)
Width	• 16.8" (426mm)
Depth	• 22.6" (574mm)
Packaging	• 24.4" (W) x 7.7" (H) x 27.4" (L)
Gross Weight	• 27 lbs (12.3kg)
Available Colors	• Black

Expansion Slots

1x full-height expansion slot (Riser card required)

Drive Bays

Hot-swap	• 2x Hot-swap SAS / SATA Drive Bays • SAS or enterprise SATA HDD only recommended
-----------------	--

SAS / SATA Backplane

1x 1U SAS / SATA Backplane With SES2

Peripheral Drives

CD-ROM	• Slim CD-ROM drive (Optional)
---------------	--------------------------------

Front Panel

Buttons	• Power On/Off button • System Reset button
LEDs	• Power LED • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED
Ports	• 2x USB ports

Motherboard (for CSE-811TQ-441B)

H8SCM	H8SCM-F
H8SGL	H8SGL-F
H8SML-7	H8SML-7F
H8SML-i	H8SML-iF
X10SL7-F	X10SLH-F
X10SLL+-F	X10SLL-F
X10SLM+-F	X10SLM+-LN4F
X10SLM-F	X11SSL
X11SSL-F	X11SSM
X11SSM-F	X9SCI-LN4
X9SCL	X9SCL+-F
X9SCL-F	X9SCM
X9SCM-F	X9SCM-iiF
X9SRi	X9SRi-3F
X9SRi-F	

System Cooling

Fans	• 2x 10cm high-performance cooling fans
-------------	---

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply

440W/480W High-Efficiency Power Supply w/PMBus 1.2, I2C, and PFC

AC Input	• 100-140V, 50-60Hz, 5.5-4A • 180-240V, 50-60Hz, 3.5-2.5A
DC Output	• +3.3V: 15A • +5V: 18A • +5V standby: 3A • +12V: 35.8A at 100-140Vac 39.1A at 180-240Vac

Certification



Platinum Certified

[\[Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC	• USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark
----------------------------------	--

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc811tq-441b-1u-2xlff-fix-psu-p-2233.html>