

Supermicro SuperChassis SC813LT-R500CB 1U 2xLFF RED PSU

Kod producenta: CSE-813LT-R500CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	2
Power Supply	Redundant
PSU Wattage	500W
PSU Certification	80+ Platinum

Product SKUs

CSE-813LT-R500CB • SuperChassis 813LT-R500CB

Form Factor

1U chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 1.7" (43mm)
Width • 17.2" (437mm)
Depth • 25.6" (650mm)
Gross Weight • 36 lbs (16.4kg)
Package 23.5" x 8.5" x 33.7"
Available Colors • Black

Expansion Slots

• 1x Full-height, Full-length PCI expansion slot

Drive Bays

Hot-swap • 2x 3.5" SAS/SATA hot-swap drive trays
• SAS or enterprise SATA HDD only recommended

SATA Backplane

1x 1U SAS / SATA backplane

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
LEDs • Hard drive activity LED
• 2x Network activity LEDs
• System Information LED

System Cooling

Fans • 2x 10cm PWM blower fans

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

500W Redundant High-Efficiency Power Supplies w/ Power Distributor, PMBus 1.2, I²C, and PFC

AC Input • 100-240V, 50-60Hz, 6.1-2.6A
DC Output • +5V standby: 3A
• +12V: 42A
• +5V: 25A
With Power Distributor • +3.3V: 12A
• -12V: 0.6A

Certification



Platinum Certified

[[Test Report](#)]

Regulatory (Power Supply)

• USA - UL listed, FCC
• Canada - CUL listed
• China - CCC Mark
Power Supply Safety / EMC • Europe/CE Mark
• EN 60950/IEC 60950-Compliant
• Germany - TUV Certified
• Taiwan - PSMI Mark

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813lt-r500cb-1u-2xlff-red-psu-p-2239.html>