

# Supermicro SuperChassis SC813MTQ-441CB 1U 4xLFF FIX PSU

Kod producenta: CSE-813MTQ-441CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	440W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 503mm

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs

CSE-813MTQ-441CB • SuperChassis 813MTQ-441CB (Black)

## Form Factor

1U chassis support for max. motherboard size - 12" x 10" ATX

## Processor Support

Supports dual, single Intel® / AMD processors

## Dimensions

Height • 1.7" (43mm)  
Width • 17.2" (437mm)  
Depth • 19.8" (503mm)  
Packaging • 23.4" (W) x 8.5" (H) x 29.7" (L)  
Gross Weight • 31 lbs (14.1kg)  
Available Colors • Black

## Expansion Slots

1x full-height expansion slot (Riser card required)

## Drive Bays

Hot-swap • 4x 3.5" Hot-swap SAS / SATA drive bays  
• SAS or enterprise SATA HDD only recommended

## SAS / SATA Backplane

1x SAS / SATA Backplane

## Peripheral Drives

DVD-ROM • Slim DVD-ROM drive (Optional)

## Front Panel

Buttons • Power On/Off button  
• System Reset button  
LEDs • Power LED  
• Hard drive activity LED  
• 2x Network activity LEDs  
• System Overheat LED  
Ports • 2x Front USB Ports  
• 1x Serial COM Port

## Motherboard (for CSE-813MTQ-441CB)

<a href="#">H8SCM</a>	<a href="#">H8SCM-F</a>
<a href="#">H8SGL</a>	<a href="#">H8SGL-F</a>
<a href="#">H8SML-7</a>	<a href="#">H8SML-7F</a>
<a href="#">H8SML-i</a>	<a href="#">H8SML-iF</a>
<a href="#">X10SL7-F</a>	<a href="#">X10SLH-F</a>
<a href="#">X10SLL+-F</a>	<a href="#">X10SLL-F</a>
<a href="#">X10SLM+-F</a>	<a href="#">X10SLM+-LN4F</a>
<a href="#">X10SLM-F</a>	<a href="#">X9DBL-3</a>
<a href="#">X9DBL-3F</a>	<a href="#">X9DBL-i</a>
<a href="#">X9DBL-iF</a>	<a href="#">X9DRL-7F</a>
<a href="#">X9DRL-EF</a>	<a href="#">X9SCL-LN4</a>
<a href="#">X9SCL</a>	<a href="#">X9SCL+-F</a>
<a href="#">X9SCL-F</a>	<a href="#">X9SCM</a>
<a href="#">X9SCM-F</a>	<a href="#">X9SCM-iiF</a>
<a href="#">X9SRi</a>	<a href="#">X9SRi-3F</a>
<a href="#">X9SRi-F</a>	

## Server(s) for SC813MTQ-441CB

[6017B-MTF](#)

## System Cooling

Fans • 4x 4cm high performance fans

## Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)  
Range  
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)  
Range  
Operating Relative Humidity • 8% ~ 90% (non-condensing)  
Range  
Non-Operating Relative Humidity • 5% - 95% (non-condensing)  
Range

## Power Supply

440W/480W High-Efficiency Power Supply w/PMBus 1.2, I2C, and PFC

AC Input • 100-140V, 50-60Hz, 5.5-4A  
• 180-240V, 50-60Hz, 3.5-2.5A  
• +3.3V: 15A  
• +5V: 18A  
• +5V standby: 3A  
DC Output • +12V:  
35.8A at 100-140Vac  
39.1A at 180-240Vac

Certification



Platinum Certified

[ [Test Report](#) ]

## Regulatory (Power Supply)

Power Supply • USA - UL listed, FCC  
Safety / EMC • Canada - CUL listed  
• Europe/CE Mark

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mtq-441cb-1u-4xlff-fix-psu-p-2249.html>