

# Supermicro SuperChassis SC815TQ-563UB 1U 4xLFF FIX PSU

Kod producenta: CSE-815TQ-563UB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	560W
PSU Certification	80+ Platinum

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs

CSE-815TQ-563UB • SuperChassis 815TQ-563UB (Black)

## Form Factor

1U chassis support for max. UIO motherboard size - 12" x 13" and 13.68" x 13"

## Processor Support

Supports dual Intel® / AMD processors

## Dimensions

Height • 1.7" (43mm)  
Width • 17.2" (437mm)  
Depth • 25.6" (650mm)  
Gross Weight • 36 lbs (16.4kg)  
Available Colors • Black

## Expansion Slots

- 1x Full-height Universal I/O Expansion Slot
- 1x Full-height, Full-length PCI Expansion Slot
- 1x Low-profile PCI Expansion Slot

## Drive Bays

Hot-swap • 4x 3.5" SAS / SATA Hot-swap drive trays  
• SAS or enterprise SATA HDD only recommended

## SAS / SATA Backplane

1x 1U SAS / SATA backplane

## Peripheral Drives

DVD-ROM • Slim DVD-ROM drive (Optional)

## Front Panel

Buttons • Power On/Off button  
• System Reset button  
LEDs • Power LED  
• Hard drive activity LED  
• 2x Network activity LEDs  
• System Overheat LED  
Ports • 2x USB & DB9 COM port tray  
• (Optional - in place of floppy drive)

## Motherboard (for CSE-815TQ-563UB )

[H8DGU](#)  
[X8DTU](#)

[H8DGU-F](#)  
[X8SIU-F](#)

## System Cooling

Fans • 4x 4cm Counter-rotating PWM fans

## Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)  
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)  
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)  
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

## Power Supply

560W AC power supply w/ PFC (20-pin)  
AC Voltage • 100-240 V, 50-60 Hz, 7.5 Amp max  
+5V • 18 Amp  
+5V standby • 3 Amp  
+12V • 46 Amp @ 100-180V;  
49 Amp @ 180-240V  
-12V • 0.5 Amp  
+3.3V • 15 Amp

Certification



[Gold Certified](#)

## Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC  
• Canada - CUL listed  
• China - CCC Mark  
• Europe/CE Mark  
• EN 60950/IEC 60950-Compliant  
• Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc815tq-563ub-1u-4xlf-fix-psu-p-2266.html>

Copyright ©2024 www.superstorage.pl | czwartek, 21 listopad 2024

Strona: 2 / 3

