

Supermicro SuperChassis SC815TQ-R700UB 1U 4xLFF RED PSU

Kod producenta: CSE-815TQ-R700UB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	700 W
PSU Certification	80+ Gold



Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-815TQ-R700UB • SuperChassis 815TQ-R700UB (Black)

Form Factor

1U chassis support for max. motherboard size - 12" x 13" E-ATX

- Optimized for Universal I/O (UIO) motherboards

Processor Support

Supports single, dual Intel® Xeon® processor 5500 Series (Tylersburg/Nehalem) / AMD Opteron™ processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 25.6" (650mm)
- Gross Weight • 36 lbs (16.3kg)
- Package • 23.5" x 8.5" x 33.7"
- Available Colors • Black

Expansion Slots

- 1x Full-height Universal I/O Expansion Slot (Riser Card Required)
- 1x Full-height, Full-length PCI Expansion Slot (Riser Card Required)
- 1x Low-profile PCI Expansion Slot (Riser Card Required)

Drive Bays

- Hot-swap • 4x 3.5" SAS / SATA Hot-swap drive trays
- SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 1U SAS / SATA backplane

Peripheral Drives

- DVD-ROM • Slim DVD-ROM drive (optional)

Front Panel

- Buttons
 - Power On/Off Button
 - System Reset Button
 - UID Button
- LEDs
 - Power LED
 - Hard drive activity LED
 - 2x Network activity LEDs
 - Universal Information (UID) LED
- Ports
 - 2x USB & DB9 COM port tray
 - (Optional - in place of floppy drive)

Motherboard (for CSE-815TQ-R700UB)

[H8DGU](#)
[X8DTU](#)

[H8DGU-F](#)

System Cooling

- Fans • 4x 4cm Counter-rotating PWM fans

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

- 700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C
- AC Voltage
 - 700W: 100 - 140 V, 50-60 Hz, 8.5-6 Amp
 - 750W: 180 - 240V, 60-50 Hz, 5-3.8 Amp
- DC Output +5V standby • 3 Amp
- DC Output +12V
 - 700W: 58 Amp @ 100-140V
 - 750W: 62 Amp @ 180-240V
- With Power Distributor
 - +5V: 25 Amp
 - +3.3V: 12 Amp
 - -12V: 0.6 Amp

Certification



[Gold Certified](#)

Regulatory (Power Supply)

- USA - UL listed, FCC
- Canada - CUL listed
- Power Supply Safety / EMC
 - China - CCC Mark
 - Europe/CE Mark
 - EN 60950/IEC 60950-Compliant
 - Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc815tq-r700ub-1u-4xlf-red-psu-p-2272.html>