

# Supermicro SuperChassis SC213AC-R920WB 2U 16xSFF RED PSU

Kod producenta: CSE-213AC-R920WB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum
Uwagi	Single Expander SAS3 Backplane



*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs

CSE-213AC-R920WB • SuperChassis  
213AC-R920WB (black)

## Form Factor

2U rackmount chassis - supports for maximum motherboard sizes: 13.68" x 13"; E-ATX, ATX

## Processor Support

Dual and Single Intel® and AMD processors

## Dimensions

Height 3.5" (89mm)  
Width 17.2" (437mm)  
Depth 24.8" (630mm)  
Packaging 27" (W) x 14.8"(H) 37.3" (L)  
Gross Weight 60 lb (27.22 kg)  
Available Colors black

## Expansion Slots

- 4 full height expansion slot(s)
- 3 low-profile expansion slot(s)

## Drive Bays

**Hot-swap** 16x 2.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards

## Backplane

- BPN-SAS3-213A

## Peripheral Drives

- 1 Optional standard 5.25" drive bay
- 1 Optional USB + COM port tray
- 1 Optional slim DVD-ROM drive bay

## Front Panel

- Buttons**
- Power On/Off button
  - System Reset Button
  - 2 Network Activity LEDs
- LEDs**
- HDD activity LED
  - Power Status LED
  - Power Fail LED
  - System Information LED

## Motherboard (for CSE-213AC-R920WB )

[X10DRW-i](#)

[X10DRW-iT](#)

## System Cooling

**Fans** 3x 8cm high-performance PWM fans

## System Monitoring

Chassis intrusion switch

## Operating Environment (System)

Operating Temperature Range 5°C - 35°C (41°F - 95°F)  
Non-Operating Temperature Range -40°C - 70°C (-40°F - 158°F)  
Operating Relative Humidity Range 8% - 90% (non-condensing)  
Non-Operating Relative Humidity Range 5% - 95% (non-condensing)

## Power Supply with Power Distributor

920W high-efficiency (94%+) AC-DC Redundant power supplies with PMBus and I2C  
AC Input • 100-240 V, 50-60 Hz, 11-4.5 Amp  
DC Output • 4 Amp @ +5V standby  
• 75 Amp @ +12V

Certification



**Platinum Certified**

[ [Test Report](#) ]

## Regulatory (Power Supply)

- Power Supply Safety / EMC**
- USA - UL listed
  - Canada - CUL listed
  - Germany - TUV Certified
  - EN 60950/IEC 60950-Compliant
  - CB Report
  - CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc213ac-r920wb-2u-16xsff-red-psu-p-2276.html>

Copyright ©2024 www.superstorage.pl | czwartek, 21 listopad 2024

Strona: 2 / 3

