

Supermicro SuperChassis SC213A-R740LPB 2U 16xSFF RED PSU

Kod producenta: CSE-213A-R740LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	740W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-213A-R740LPB • SuperChassis 213A-R740LPB (black)

Form Factor

2U chassis support for max. motherboard size - 13" x 13.68",
E-ATX and ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width • 17.2" (437mm)
Height • 3.5" (89mm)
Depth • 24.8" (630mm)
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)
Weight • Gross: 50 lbs (22.7kg) / Net: 46 lbs (20.9kg)
Available Color • Black

Expansion Slots

• 7x low-profile expansion slots

Drive Bays

Hot-swap 16x 2.5" SAS / SATA Hot-swap drive bays
SAS or enterprise SATA HDD only recommended

Peripheral Bay 1x 5.25" peripheral Drive Bay
1x Slim Optical Drive Bay
1x USB/COM Port Bay

Backplane

2U Direct Attached Backplane, features:
• 3Gb/6Gb support
• SES-2 Enclosure Management Support
• SAS/SATA support
• Four SFF 8087 connectors

Peripheral Drives

DVD-ROM 1x Slim DVD-ROM Drive, 2x USB + 1x COM port (option)

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
• Hard drive activity LED

LEDs • 2x Network activity LEDs
• System Information LED
• Power fail LED

Motherboard (for CSE-213A-R740LPB)

H8DG6	H8DG6-F
H8DGi	H8DGi-F
H8SCM	H8SCM-F
X10DAC	X10DAi
X10DRi	X10DRi-LN4+
X10DRi-T	X10DRi-T4+
X10SRH-CLN4F	X9DA7
X9DAE	X9DAi
X9DB3-F	X9DB3-TPF
X9DBi-F	X9DBi-TPF
X9DR3-F	X9DR3-LN4F+
X9DR7-TF+	X9DRD-7LN4F
X9DRD-7LN4F-JBOD	X9DRD-EF
X9DRE-LN4F	X9DRE-TF+
X9DRH-7F	X9DRH-7TF
X9DRH-iF	X9DRH-iF-NV
X9DRH-iTF	X9DRi-F
X9DRi-LN4F+	X9SCI-LN4
X9SCL	X9SCL+-F
X9SCL-F	X9SCM
X9SCM-F	X9SCM-iiF
X9SRE	X9SRE-3F
X9SRE-F	X9SRi
X9SRi-3F	X9SRi-F
X9SRL-F	

System Cooling

Fans 3x 80mm 7,000 RPM 4-pin PWM fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range

Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range

Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range

Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply with Power Distributor

740W (1+1) Redundant high-efficiency power supply with PMBus

AC Input • 100-240 V, 50-60 Hz, 9-3.5 Amp

DC Output • 4 Amp @ +5V standby
• 61.7 Amp @ +12V

With Power Distributor • +5V: 45 Amp
• +3.3V: 24 Amp
• -12V: 0.6 Amp



Certification

Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- FCC certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc213a-r740lpb-2u-16xsff-red-psu-p-2287.html>