

# Supermicro SuperChassis SC213LTQ-R720LPB 2U 8xSFF RED PSU

Kod producenta: CSE-213LTQ-R720LPB



|                        |           |
|------------------------|-----------|
| Chassis Form Factor    | Rack 2U   |
| # of 2.5 hot-swap bays | 8         |
| Power Supply           | Redundant |
| PSU Wattage            | 720W      |
| PSU Certification      | 80+ Gold  |

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs

---

CSE-213LTQ-R720LPB • SuperChassis  
213LTQ-R720LPB (black)

## Form Factor

---

2U chassis support for motherboard size -  
13.68" x 13", E-ATX and ATX

## Processor Support

---

Supports dual, single Intel® / AMD processors

## Dimensions

---

Width • 17.2" (437mm)  
Height • 3.5" (89mm)  
Depth • 24.8" (630mm)  
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)  
Weight • Gross: 50 lbs (22.7kg) / Net: 46 lbs (20.9kg)  
Available Color • Black

## Expansion Slots

---

• 7x Low-profile expansion slots

## Drive Bays

---

**HDD** 8x 2.5" Hot-swap SAS/SATA HDD bays for SAS or enterprise SATA HDD only  
**Peripheral** 1x 5.25" peripheral drive bay

## Backplane

---

2U Direct Attached Backplane, features:

- 3Gb/6Gb support
- SES-2 Enclosure Management Support
- SAS/SATA support

## Front Panel

---

**Buttons** • Power On/Off button  
• System Reset button  
• Power LED  
• Hard drive activity LED  
**LEDs** • 2x Network activity LEDs  
• System Information LED  
• Power fail LED

## System Cooling

---

**Fans** 3x 80x38mm high-performance, high-quality PWM fans

## System Monitoring

---

Chassis intrusion switch

## Operating Environment (System)

---

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)  
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)  
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)  
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

## Power Supply with Power Distributor

---

720W (1+1) Redundant high-efficiency power supply with PMBus

AC Input • 100-240 V, 50-60 Hz, 4-9 Amp  
DC Output • 3 Amp @ +5V standby  
• 59 Amp @ +12V  
• +5V: 45 Amp  
• +3.3V: 24 Amp  
• -12V: 0.6 Amp

Certification



**Gold Certified**  
[ [Test Report](#) ]

## Regulatory (Power Supply)

---

**Power Supply Safety / EMC** • USA - UL listed  
• Canada - CUL listed  
• Germany - TUV Certified  
• EN 60950/IEC 60950-Compliant  
• CB Report  
• CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc213ltq-r720lpb-2u-8xsff-red-psu-p-2291.html>