

Supermicro SuperChassis SC216E16-R1200LPB 2U 24xSFF RED PSU

Kod producenta: CSE-216E16-R1200LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Gold
Uwagi	Single Expander SAS2 Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-216E16-R1200LPB)	
CSE-216E16-R1200LPB • SuperChassis 216E16-R1200LPB (Black)	H8DG6	H8DG6-F
	H8DGi	H8DGi-F
	X8DA6	X8DAE
	X8DTH-i	X8DTH-iF
	X8DTL-6	
Form Factor		
2U chassis support for motherboard size - 13.68" x 13", E-ATX and ATX		
Processor Support	System Cooling	
Supports dual, single Intel® / AMD processors	Fans	3x 80mm 7000 RPM hot-swap PWM fans
Dimensions	System Monitoring	
Width • 17.2" (437mm)	Chassis intrusion switch	
Height • 3.5" (89mm)		
Depth • 24.8" (630mm)	Operating Environment (System)	
Packaging • 26.5" (W) x 10.5" (H) x 38" (L)	Operating	
Weight • Net Weight: 35 lbs (15.9kg)	Temperature • 5°C ~ 35°C (41°F ~ 95°F)	
• Gross Weight: 57 lbs (25.9kg)	Range	
Available Color Black	Non-Operating	
	Temperature • -40°C ~ 60°C (-40°F ~ 140°F)	
Expansion Slots	Range	
• 7x low-profile expansion slots	Operating	
	Relative	
Drive Bays	Humidity • 8% ~ 90% (non-condensing)	
	Range	
Hot-swap 24x 2.5" SAS / SATA Hot-swap drive trays	Non-Operating	
SAS or enterprise SATA HDD only recommended	Relative	
	Humidity • 5% - 95% (non-condensing)	
	Range	
Backplane	Power Supply	
SAS2 Expander Backplane, features:	Redundant 1200W high-efficiency power supply with PMBus	
• Scalability through cascading	AC Input	
• 6Gb SAS2/SATA3 HDD support	• 1000W Output @ 100-140V, 11.5-8A, 50-60Hz	
• Inband SES-2 Enclosure Management	• 1200W Output @ 180-240V, 8-5.5A, 50-60Hz	
• Single input/output SFF 8087 connectors	DC Output	
	• 1000W: +12V/83A; +5Vsb/4A	
	• 1200W: +12V/100A; +5Vsb/4A	
Front Panel	DC Output	
Buttons • Power On/Off button	• +5V: 50 Amp	
• System Reset button	• +3.3V: 30 Amp	
	• -12V: 0.6 Amp	
LEDs • Hard drive activity LED	Certification	
• 2x Network activity LEDs		
• System Overheat LED	Gold Certified	
• Power fail LED	[Test Report]	
	Regulatory (Power Supply)	
	Power Supply Safety / EMC	
	• USA - UL listed	
	• Canada - CUL listed	
	• Germany - TUV Certified	
	• EN 60950/IEC 60950-Compliant	
	• CB Report	
	• CCC Certification	

<https://www.superstorage.pl/supermicro-superchassis-sc216e16-r1200lpb-2u-24xsff-red-psu-p-2304.html>