

Supermicro SuperChassis SC216BA-R920WB 2U 24xSFF RED PSU

Kod producenta: CSE-216BA-R920WB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	920 W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	
CSE-216BA-R920WB	• SuperChassis 216BA-R920WB (Black)
Form Factor	
2U chassis support for max. motherboard size - 13" x 13.68", E-ATX and ATX	
Processor Support	
Supports dual, single Intel® / AMD processors	
Dimensions	
Width	• 17.2" (437mm)
Height	• 3.5" (89mm)
Depth	• 24.8" (630mm)
Packaging	• 26.5" (W) x 10.5" (H) x 38" (L)
Gross Weight	53 lbs (24kg)
Available Color	Black
Expansion Slots	
• 7x low-profile expansion slots	
Drive Bays	
Hot-swap	24x 2.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended
Backplane	
2U Direct Attached Backplane, features: • 3Gb/6Gb support • SES-2 Enclosure Management Support • SAS/SATA support • Six SFF 8087 connectors	

Front Panel	
Buttons	• Power On/Off button • System Reset button
LEDs	• Power LED • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED • Power fail LED

Motherboard (for CSE-216BA-R920WB)	
X10DDW-i	X10DDW-iN
X10DRW-E	X10DRW-ET
X10DRW-i	X10DRW-iT
X10DRW-N	X10DRW-NT

System Cooling	
Fans	3x 80mm 7000 RPM PWM fans

System Monitoring	
Chassis intrusion switch	

Operating Environment (System)	
Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply	
920W Redundant High-Efficiency Power Supplies w/ Power Distributor, PMBus 1.2, I²C, and PFC	
AC Input	• 100-240 V, 50-60 Hz, 11-4.5 Amp
DC Output	• +5V standby: 4A • +12V: 75A
With Power Distributor	• +5V: 45A • +3.3V: 24A • -12V: 0.6A

Certification	 Platinum Certified [Test Report]
---------------	---

Regulatory (Power Supply)	
Power Supply Safety / EMC	• USA - UL listed • Canada - CUL listed • Germany - TUV Certified • EN 60950/IEC 60950-Compliant • CB Report • CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc216ba-r920wb-2u-24xsff-red-psu-p-2311.html>