

Supermicro SuperChassis SC219A-R920WB 2U 16xSFF RED PSU

Kod producenta: CSE-219A-R920WB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	920 W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-219A-R920WB • SuperChassis 219A-R920WB (Black)

Form Factor

2U chassis supports Supermicro Proprietary WIO motherboards:
Max. motherboard size - 13.68" x 16.5"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 3.5" (89mm)
Width 17.2" (437mm)
Depth 26.93" (684mm)
Gross Weight 61 lb (27.67 kg)
Packaging 25.7" (W) x 10.8"(H) x 39.3" (D)
Available Color black

Expansion Slots

- 4x Full-height, Full-length Expansion Slots
- 3x Low-profile Expansion Slots

Drive Bays

Hot-swap 16x 2.5" SAS / SATA Hot-swap drive trays
SAS or enterprise SATA HDD only recommended

Peripheral Bay 1x 5.25" peripheral drive bay

Backplane

2U Direct Attached Backplane, features:
• 3Gb/6Gb support
• SES-2 Enclosure Management Support
• SAS/SATA support
• Four SFF 8087 connectors

Peripheral Drives

DVD-ROM 1x Slim DVD-ROM Drive (option)
1x Front USB + COM tray (option)

Front Panel

Buttons

- Power On/Off button
- System Reset button
- Power LED
- Hard drive activity LED

LEDs

- 2x Network activity LEDs
- System Information LED
- Power fail LED

Motherboard (for CSE-219A-R920WB)

[X9DRW-3LN4F+](#) [X9DRW-3TF+](#)
[X9DRW-7TPF+](#) [X9DRW-iTPF](#)
[X9DRW-iTPF+](#)

Server(s) for SC219A-R920WB

[2027R-N3RF4+](#) [2027R-72RFTP+](#)
[2027R-N3RFT+](#)

System Cooling

Fans

- 4x 80mm high-performance fans
- Optional extra 3x 80mm fans support cooling redundancy for E-ATX motherboards

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply with Power Distributor

920W high-efficiency (94%+) AC-DC Redundant power supplies with PMBus and I2C
AC Input • 100-240 V, 50-60 Hz, 11-4.5 Amp
DC Output • 4 Amp @ +5V standby
• 75 Amp @ +12V

Certification  **Platinum Certified**
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc219a-r920wb-2u-16xsff-red-psu-p-2323.html>