

Supermicro SuperChassis SC825TQ-R740LPB 2U 8xLFF RED PSU

Kod producenta: CSE-825TQ-R740LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	740W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-825TQ-R740LPB • SuperChassis 825TQ-R740LPB (Black)

Form Factor

2U chassis support for motherboard size - 12" x 13", 13.68" x 13" E-ATX and 12" x 10" ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 3.5" (89mm)
Width 17.2" (437mm)
Depth 25.5" (648mm)
Gross Weight 52 lbs (23.6 kg)
Available Color Black

Expansion Slots

• 7x low-profile full-length expansion slots

Drive Bays

Hot-swap 8x 3.5" SAS / SATA Hot-swap drive bays
SAS or enterprise SATA HDD only recommended

SAS Backplane

1x 2U SAS backplane w/ Enclosure Management

Peripheral Drives

DVD-ROM Slim DVD-ROM drive (Optional)

Front Panel

Buttons • Power On/Off button
• System Reset button
• Power LED
LEDs • Hard drive activity LED
• 2x Network activity LEDs
• System Overheat LED
• Power fail LED
Ports 2x USB Ports + DB9 COM Port (optional)

Motherboard (for CSE-825TQ-R740LPB)

H8SCM H8SCM-F
X10DAC X10DAI
X10DAX X10DRi
X10DRi-LN4+ X10DRi-T
X10DRi-T4+ X10DRi-C
X10DRi-CT X10DRi-i
X10DRi-3T X10DRi-LN4
X9DA7 X9DAE
X9DAi X9DB3-F
X9DB3-TPF X9DBi-F
X9DBi-TPF X9DR3-F
X9DR3-LN4F+ X9DRD-7LN4F
X9DRD-7LN4F-JBOD X9DRD-EF
X9DRD-iF X9DRD-LF
X9DRE-LN4F X9DRH-7F
X9DRH-7TF X9DRH-iF
X9DRH-iF-NV X9DRH-3TF
X9DRi-F X9DRi-LN4F+
X9SCL-LN4 X9SCL
X9SCL-F X9SCL-F
X9SCM X9SCM-F
X9SCM-iiF X9SRE
X9SRE-3F X9SRE-F
X9SRi X9SRi-3F
X9SRi-F X9SRi-LF

Server(s) for SC825TQ-R740LPB

6027R-3RF4+ 6027R-72RF
6027R-72RFT+ 6027R-TRF
6027R-72RFT 6028R-TRT
6028R-TR 6027R-73DARF
6027R-TDARF

System Cooling

Fans 3x 80x38mm 4-pin PWM Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply with Power Distributor

740W (1+1) Redundant high-efficiency power supply with PMBus
AC Input • 100-240 V, 50-60 Hz, 9-3.5 Amp
• 4 Amp @ +5V standby
DC Output • 61.7 Amp @ +12V
• +5V: 30 Amp
With Power Distributor • +3.3V: 24 Amp
• -12V: 0.6 Amp



Certification Platinum Certified [Test Report]

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed
• Canada - CUL listed
• Germany - TUV Certified
• EN 60950/IEC 60950-Compliant
• CB Report
• CCC Certification

Strona firmowa produktu:

https://www.superstorage.pl/supermicro-superchassis-sc825tq-r740lpb-2u-8x1ff-red-psu-p-2352.html