

Supermicro SuperChassis SC825TQ-R740WB 2U 8xLFF RED PSU

Kod producenta: CSE-825TQ-R740WB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	740W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-825TQ-R740WB • SuperChassis 825TQ-R740WB (Black)

Form Factor

2U chassis supports Supermicro Proprietary WIO motherboards

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 3.5" (89mm)
Width 17.2" (437mm)
Depth 25.5" (648mm)
Gross Weight 52 lbs (23.6 kg)
Available Color Black

Expansion Slots

• 4x Full-height Full-length I/O and 3x Low-Profile Expansion Slots
(Standard add-on cards)

Drive Bays

8x 3.5" SAS / SATA Hot-swap drive bays
Hot-swap SAS or enterprise SATA HDD only recommended

SAS Backplane

1x 2U SAS backplane w/ Enclosure Management

Peripheral Drives

DVD-ROM Slim DVD-ROM drive (Optional)

Front Panel

Buttons

- Power On/Off button
- System Reset button
- Power LED
- Hard drive activity LED

LEDs

- 2x Network activity LEDs
- System Information LED
- Power fail LED

Ports 2x USB Ports + DB9 COM Port (optional)

Motherboard (for CSE-825TQ-R740WB)

[X10DDW-i](#) [X10DDW-iN](#)
[X10DRW-E](#) [X10DRW-ET](#)
[X10DRW-i](#) [X10DRW-iT](#)
[X10DRW-N](#) [X10DRW-NT](#)
[X10SRW-F](#) [X9DRW-3F](#)
[X9DRW-iF](#)

Server(s) for SC825TQ-R740WB

[6027R-N3RE](#) [6028R-WTR](#)
[6028R-WTRT](#) [6027R-WRF](#)

System Cooling

Fans 3x 80x38mm 4-pin PWM Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply with Power Distributor

740W (1+1) Redundant high-efficiency power supply with PMBus
AC Input • 100-240 V, 50-60 Hz, 9-3.5 Amp
DC Output • 4 Amp @ +5V standby
• 61.7 Amp @ +12V
With Power Distributor • +5V: 30 Amp
• +3.3V: 24 Amp
• -12V: 0.6 Amp

Certification



Platinum Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc825tq-r740wb-2u-8x1ff-red-psu-p-2353.html>

