

Supermicro SuperChassis SC836TQ-R800B 3U 16xLFF RED PSU

Kod producenta: CSE-836TQ-R800B



Chassis Form Factor	Rack 3U
# of 3.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	800W

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

- SuperChassis 836TQ-R800V (CSE-836TQ-R800V **Silver**): OEM only *
- SuperChassis 836TQ-R800B (CSE-836TQ-R800B **Black**)

Form Factor

3U chassis support for max. motherboard size - 13.68" x 13"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height	5.2" (132mm)
Width	17.2" (437mm)
Depth	25.5" (648mm)
Gross Weight	55 lbs (25kg)
Available Colors	Black, Silver (OEM) *

Expansion Slots

- 7x full-height full-length expansion slots

Drive Bays

Hot-swap	16x 3.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended
-----------------	---

Backplane

3U Direct Attached Backplane, features:

- 3Gb/6Gb support
- SES-2 Enclosure Management Support
- SAS/SATA support
- 16 SATA connectors

Peripheral Drives

DVD-ROM	Slim DVD-ROM Drive
Floppy	Slim 1.44MB Floppy Drive (Optional)

Front Panel

Buttons	<ul style="list-style-type: none">• Power On/Off button• System Reset button
LEDs	<ul style="list-style-type: none">• Power LED• Hard drive activity LED• 2x Network activity LEDs• System Overheat LED• Power fail LED
Ports	2x USB Ports & DB9 COM Port

Exception caught! Variable PRODID is undefined.

System Cooling

- | | |
|-------------|---|
| Fans | <ul style="list-style-type: none">• 3x 80mm Hot-swap PWM Fans• 2x 80mm Rear-exhaust Fans |
|-------------|---|

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range	• 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	• -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	• 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	• 5% - 95% (non-condensing)

Power Supply and Distributor

800W (1 + 1) Redundant AC-DC high-efficiency power supply w/ PFC	
AC Voltage	• 100 - 240V, 50-60Hz, 10-4 Amp
+5V standby	• 4 Amp
+12V	• 66 Amp
With Power Distributor	<ul style="list-style-type: none">• +5V: 30 Amp• +3.3V: 24 Amp• -12V: 0.6 Amp

Regulatory (Power Supply)

Power Supply Safety / EMC	<ul style="list-style-type: none">• USA - UL listed• Canada - CUL listed• Germany - TUV Certified• EN 60950/IEC 60950-Compliant• CB Report• CCC Certification
----------------------------------	--

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc836tq-r800b-3u-16xlf-red-psu-p-2372.html>