

Supermicro SuperChassis SC833T-653B 3U 8xLFF FIX PSU

Kod producenta: CSE-833T-653B



Chassis Form Factor	Rack 3U
# of 3.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	650W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-833T-653B • SuperChassis 833T-653B (Black)

Form Factor

3U chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 5.2" (132mm)

Width 17.7" (450mm)

Depth 25.5" (648mm)

Gross Weight 69 lbs (31.3kg)

Available Colors Black

Expansion Slots

- 6x PCI expansion slots
- SIMLC Support Only

Drive Bays

Hot-swap • 8x 3.5" SATA Hot-swap Drive Bay
• SAS or enterprise SATA HDD only recommended

Peripheral Bay(s) • 2x 5.25" Peripheral Drive Bay
• 1x 3.5" Drive Bay
• 1x Slim CDROM Drive Bay

Peripheral Drives

Floppy Sony 3.5" 1.44MB Floppy Drive (optional)

DVD-ROM Slim DVD-ROM drive (optional)

SATA Backplane

SATA Backplane

Front Panel

Buttons • Power On/Off button
• System Reset button
• Alarm Mute Switch

LEDs • Power LED
• Hard drive activity LED
• 2x Network activity LEDs
• System Overheat LED

Ports none (Optional front USB ports via 5.25" drive bay)

Motherboard (for CSE-833T-653B)

- | | |
|-------------------------------|------------------------------|
| H8DCL-6 | H8DCL-6F |
| H8DCL-i | H8DCL-iF |
| H8SCM | H8SCM-F |
| H8SML-7 | H8SML-7F |
| H8SML-i | H8SML-iF |
| X10DRL-C | X10DRL-CT |
| X10DRL-i | X10DRL-iT |
| X10DRL-LN4 | X10SL7-F |
| X10SLH-F | X10SLL+-F |
| X10SLL-F | X10SLL-S |
| X10SLL-SF | X10SLLM+-F |
| X10SLLM+-LN4F | X10SLLM-F |
| X10SRH-CF | X10SRH-CLN4F |
| X10SRi-F | X10SRL-F |
| X11SSA-F | X9DBL-3 |
| X9DBL-3F | X9DBL-i |
| X9DBL-iF | X9DRL-3F |
| X9DRL-7F | X9DRL-EF |
| X9DRL-iF | X9SRH-7F |
| X9SRH-7TF | |

System Cooling

- 4 9cm 5,000 RPM Hot-swap PWM Fans
- 2 8cm 5,000 RPM Rear Exhaust PWM Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

- Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
- Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
- Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
- Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

- 650W AC-DC High Efficiency Power Supply
- AC Input • 100 - 140V, 8-5.2A 180-240V
4.2-3.1A, 50-60Hz
- +5V • 30 Amp
- +5V standby • 4 Amp
- +12V • 100-140Vac 49Amp
180-240Vac 54Amp
- 12V • 0.5 Amp
- +3.3V • 25 Amp

Certification



Gold Certified

Regulatory (Power Supply)

- Power Supply Safety / EMC**
- USA - UL listed, FCC
 - Canada - CUL listed
 - Germany - TUV Certified
 - Europe/CE Mark
 - EN 60950/IEC 60950-Compliant
 - CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc833t-653b-3u-8x1ff-fix-psu-p-2376.html>