


Supermicro SuperChassis SC745TQ-920B Tower/4U 8xLFF FIX PSU

Kod producenta: CSE-745TQ-920B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	920W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	Motherboard (for CSE-745TQ-920B)	
CSE-745TQ-920B • SuperChassis 745TQ-920B (Black)	C7B75	C7Z87-OCE
Form Factor	H8DG6	H8DG6-F
Tower / 4U chassis support for max. motherboard size - 13.68" x 13" (34.7cm x 33cm), ATX, E-ATX	H8DGi	H8DGi-F
	H8SCM	H8SCM-F
	H8SGL	H8SGL-F
Processor Support	X10SAE	X10SAT
Supports dual, single Intel® / AMD processors	X10SL7-F	X10SLA-F
	X10SLH-F	X10SLL+-F
	X10SLL-F	X10SLL-S
Dimensions	X10SLL-SF	X10SLM+-F
Height • 17.8" (452mm)	X10SLM+-LN4F	X10SLM-F
Width • 7.0" (178mm)	X8S16-F	X9SCL-LN4
Depth • 25.5" (648mm)	X9SCL	X9SCL+-F
Gross Weight • 58 lbs (26.3kg)	X9SCL-F	X9SCM
Available Colors • Black	X9SCM-F	X9SCM-iiF
	X9SRi	X9SRi-3F
Expansion Slots	X9SRi-F	X9SRL-F
7x PCI expansion slots		
Drive Bays	System Cooling	
Hot-swap	<ul style="list-style-type: none"> • 3x 5000 RPM Hot-swap PWM Cooling Fans 	
Peripheral Bay(s)	Fans	<ul style="list-style-type: none"> • 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans
	System Monitoring	
SAS / SATA Backplane	Chassis intrusion switch	
SAS / SATA Hard Drive Backplane with SES2	Operating Environment (System)	
Front Panel	Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F) Range	
Buttons	Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F) Range	
LEDs	Operating Relative Humidity • 8% ~ 90% (non-condensing) Range	
Ports	Non-Operating Relative Humidity • 5% - 95% (non-condensing) Range	
	Power Supply with Power Distributor	
	920W high-efficiency (94+%) power supply with PMBus	
	AC Input	• 100-240 V, 50-60 Hz, 11-4.5 Amp
	DC Output	• 4 Amp @ +5V standby • 75 Amp @ +12V
	With Power Distributor	• +5V: 30 Amp • +3.3V: 24 Amp • -12V: 0.6 Amp
Certification	 Platinum Certified [Test Report]	
	Regulatory (Power Supply)	
Power Supply Safety / EMC	<ul style="list-style-type: none"> • USA - UL listed, FCC • Canada - CUL listed • China - CCC Mark • Europe/CE Mark • EN 60950/IEC 60950-Compliant • Germany - TUV Certified 	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc745tq-920b-tower4u-8xlff-fix-psu-p-2383.html>