

# Supermicro SuperChassis SC745TQ-R800B Tower/4U 8xLFF RED PSU

Kod producenta: CSE-745TQ-R800B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	800W

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

<u>Product SKUs</u>		<u>Motherboard (for CSE-745TQ-R800B )</u>	
CSE-745TQ-R800	• SuperChassis 745TQ-R800 ( <b>Beige</b> )	<a href="#">C7B75</a>	<a href="#">X10SAE</a>
CSE-745TQ-R800B	• SuperChassis 745TQ-R800B ( <b>Black</b> )	<a href="#">X10SAT</a>	<a href="#">X8DA3</a>
<u>Form Factor</u>		<a href="#">X8DA6</a>	<a href="#">X8DAE</a>
Tower / 4U chassis support for max. motherboard size - 13.68" x 13" ( 347mm x 330mm )		<a href="#">X8DAi</a>	<a href="#">X8DAL-3</a>
<u>Processor Support</u>		<a href="#">X8DAL-i</a>	<a href="#">X8DT3</a>
Supports dual, single Intel® / AMD processors		<a href="#">X8DT3-F</a>	<a href="#">X8DT3-LN4F</a>
<u>Dimensions</u>		<a href="#">X8DT6</a>	<a href="#">X8DT6-F</a>
Height	• 17.8" (452mm)	<a href="#">X8DTE</a>	<a href="#">X8DTE-F</a>
Width	• 7.0" (178mm)	<a href="#">X8DTH-6F</a>	<a href="#">X8DTH-i</a>
Depth	• 25.5" (648mm)	<a href="#">X8DTH-iF</a>	<a href="#">X8DTi</a>
Gross Weight	• 62 lbs (28kg)	<a href="#">X8DTi-F</a>	<a href="#">X8DTi-LN4F</a>
Available Colors	• Beige, Black	<a href="#">X8DTL-3</a>	<a href="#">X8DTL-3F</a>
<u>Expansion Slots</u>		<a href="#">X8DTL-6</a>	<a href="#">X8DTL-6F</a>
7x PCI expansion slots		<a href="#">X8DTL-I</a>	<a href="#">X8DTL-iF</a>
<u>Drive Bays</u>		<a href="#">X8DTN+</a>	<a href="#">X8DTN+-LR</a>
Hot-swap	• 8x 3.5" Hot-swap SAS/SATA Drive Bays • SAS or enterprise SATA HDD only recommended	<a href="#">X8SIE</a>	<a href="#">X8SIE-F</a>
Peripheral Bay(s)	• 3x 5.25" Peripheral Drive Bay	<a href="#">X8SIL</a>	<a href="#">X8SIL-F</a>
<u>SAS / SATA Backplane</u>		<a href="#">X9DRH-7F</a>	<a href="#">X9DRH-7TF</a>
SAS / SATA Hard Drive Backplane with SES2		<a href="#">X9DRH-iF</a>	<a href="#">X9DRH-iF-NV</a>
<u>Front Panel</u>		<a href="#">X9DRH-iTF</a>	
Buttons	• Power On/Off button • System Reset button • Power LED • Hard drive activity LED	<u>System Cooling</u>	
LEDs	• 2x Network activity LEDs • System Information LED • Power Fail LED	• 3x 5000 RPM Hot-swap PWM Cooling Fans	
Ports	• 2x USB 2.0 Ports	Fans • 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans	
<u>Operating Environment (System)</u>		<u>System Monitoring</u>	
Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)		Chassis intrusion switch	
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)		<u>Power Supply and Distributor</u>	
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)		800W (1 + 1) Redundant AC-DC high-efficiency power supply w/ PFC	
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)		AC Voltage • 100 - 240V, 50-60Hz, 10-4 Amp	
		+5V standby • 4 Amp	
		+12V • 66 Amp	
		With Power • +5V: 30 Amp	
		Distributor • +3.3V: 24 Amp	
		• -12V: 0.6 Amp	
		<u>Regulatory (Power Supply)</u>	
		• USA - UL listed, FCC	
		• Canada - CUL listed	
Power Supply Safety / EMC		• China - CCC Mark	
		• Europe/CE Mark	
		• EN 60950/IEC 60950-Compliant	
		• Germany - TUV Certified	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc745tq-r800b-tower4u-8x1ff-red-psu-p-2384.html>