

# Supermicro SuperChassis SC745TQ-800B Tower/4U 8xLFF FIX PSU

Kod producenta: CSE-745TQ-800B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	800W

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

<b>Product SKUs</b>	<b>Motherboard (for CSE-745TQ-800B)</b>	
CSE-745TQ-800 • SuperChassis 745TQ-800 <b>(Beige)</b>		
CSE-745TQ-800B • SuperChassis 745TQ-800B <b>(Black)</b>	<a href="#">C7B75</a>	<a href="#">C7Z87</a>
	<a href="#">C7Z87-OCE</a>	<a href="#">X10SAE</a>
<b>Form Factor</b>	<a href="#">X10SAT</a>	<a href="#">X8DA3</a>
Tower / 4U chassis support for max. motherboard size - 13.68" x 13" (34.7cm x 33cm)	<a href="#">X8DA6</a>	<a href="#">X8DAE</a>
	<a href="#">X8DAH+</a>	<a href="#">X8DAH+-F</a>
	<a href="#">X8DAi</a>	<a href="#">X8DAL-3</a>
<b>Processor Support</b>	<a href="#">X8DAL-i</a>	<a href="#">X8DT3</a>
Supports dual, single Intel® / AMD processors	<a href="#">X8DT3-F</a>	<a href="#">X8DT3-LN4F</a>
	<a href="#">X8DT6</a>	<a href="#">X8DT6-F</a>
<b>Dimensions</b>	<a href="#">X8DTE</a>	<a href="#">X8DTE-F</a>
Height • 17.8" (452mm)	<a href="#">X8DTH-6F</a>	<a href="#">X8DTH-i</a>
Width • 7.0" (178mm)	<a href="#">X8DTH-iF</a>	<a href="#">X8DTi</a>
Depth • 25.5" (648mm)	<a href="#">X8DTi-F</a>	<a href="#">X8DTi-LN4F</a>
Gross Weight • 58 lbs (26.3kg)	<a href="#">X8DTL-3</a>	<a href="#">X8DTL-3F</a>
Available Colors • Beige, Black	<a href="#">X8DTL-6</a>	<a href="#">X8DTL-6F</a>
	<a href="#">X8DTL-i</a>	<a href="#">X8DTL-iF</a>
<b>Expansion Slots</b>	<a href="#">X8DTN+-F</a>	<a href="#">X8DTN+-F-LR</a>
7x PCI expansion slots	<a href="#">X8SIE</a>	<a href="#">X8SIE-F</a>
	<a href="#">X8SIL</a>	<a href="#">X8SIL-F</a>
<b>Drive Bays</b>	<b>System Cooling</b>	
Hot-swap	<ul style="list-style-type: none"> <li>• 8x 3.5" Hot-swap SAS/SATA Drive Bays</li> <li>• SAS or enterprise SATA HDD only recommended</li> </ul>	
Peripheral Bay(s)	<ul style="list-style-type: none"> <li>• 2x 5.25" Peripheral Drive Bay</li> <li>• 1x 5.25" Bay For Floppy Drive</li> </ul>	
	<b>Fans</b>	<ul style="list-style-type: none"> <li>• 3x 5000 RPM Hot-swap PWM Cooling Fans</li> <li>• 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans</li> </ul>
<b>SAS / SATA Backplane</b>	<b>System Monitoring</b>	
SAS / SATA Hard Drive Backplane with SES2	Chassis intrusion switch	
<b>Front Panel</b>	<b>Operating Environment (System)</b>	
Buttons	<ul style="list-style-type: none"> <li>• Power On/Off button</li> <li>• System Reset button</li> </ul>	
LEDs	<ul style="list-style-type: none"> <li>• Power LED</li> <li>• Hard drive activity LED</li> <li>• 2x Network activity LEDs</li> <li>• System Overheat LED</li> <li>• Power Fail LED</li> </ul>	
Ports	<ul style="list-style-type: none"> <li>• 2x USB Ports</li> </ul>	
	<ul style="list-style-type: none"> <li>Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)</li> <li>Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)</li> <li>Operating Relative Humidity Range • 8% ~ 90% (non-condensing)</li> <li>Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)</li> </ul>	
	<b>Power Supply</b>	
	800W AC power supply w/ PFC	
	AC Voltage • 100 - 240V, 50-60Hz, 10-4 Amp	
	+5V standby • 4 Amp	
	+12V • 66 Amp	
	With Power • +5V: 30 Amp	
	Distributor • +3.3V: 24 Amp	
	• -12V: 0.6 Amp	
	<b>Regulatory (Power Supply)</b>	
	<ul style="list-style-type: none"> <li>• USA - UL listed, FCC</li> <li>• Canada - CUL listed</li> </ul>	
	<ul style="list-style-type: none"> <li>Power Supply • China - CCC Mark</li> <li>Safety / EMC • Europe/CE Mark</li> <li>• EN 60950/IEC 60950-Compliant</li> <li>• Germany - TUV Certified</li> </ul>	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc745tq-800b-tower4u-8xlf-fix-psu-p-2385.html>