

Supermicro SuperChassis SC747TQ-R1400B Tower/4U 8xLFF RED PSU

Kod producenta: CSE-747TQ-R1400B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	1400W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-747TQ-R1400B • SuperChassis
747TQ-R1400B

Form Factor

Tower / 4U chassis support for DP and UP ATX,
E-ATX motherboards: up to size 15.2" x 13.2"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width • 18.2" (462mm)
Height • 7" (178mm)
Depth • 26.5" (673mm)
Gross Weight • 62 lbs (28.1kg)
Package • 26.6" (676mm) x 17.4" (442mm) x
(W x H x D) 38.6" (981mm)
Available • Dark Gray
Color

Expansion Slots

Capable of housing 11x Full-Height, Full-Length
expansion cards

Drive Bays

Hot-swap • 8x 3.5" Hot-swap SAS/SATA Drive
Bays
• SAS or enterprise SATA HDD only
recommended
Peripheral • 3x 5.25" drive bays in storage
Bay(s) module - rotates 90° for Rackmount
• 1x 3.5" fixed drive bay

SAS / SATA Backplane

SAS / SATA Hard Drive Backplane with SES2

Front Panel

Buttons • LED Power On/Off button
• System Reset button
• Hard drive activity LED
LEDs • 2x Network activity LEDs
• System Overheat LED
• Power Fail LED
Ports • 2x Front side USB Ports

System Cooling

Fans • 4x 5000 RPM Hot-swap Cooling
Fans
• 2x 5000 RPM Hot-swap Rear
Exhaust Fan

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating
Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating
Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating
Relative • 8% ~ 90% (non-condensing)
Humidity
Range
Non-Operating
Relative • 5% - 95% (non-condensing)
Humidity
Range

Power Supply

1400W high-efficiency (1+1) redundant power
supply with PMBus
AC Input • 1100W Output @ 100-140V,
13.5-9.5A, 50-60Hz
• 1400W Output @ 180-240V,
9.5-7.0A, 50-60Hz
DC Output • 1100W: +12V/92A; +5Vsb/4A
• 1400W: +12V/116A; +5Vsb/4A
• +5V: 30 Amp
With • +3.3V: 24 Amp
Distributor • -12V: 0.6 Amp



Certification

Gold Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply • USA - UL listed, FCC
Safety / EMC • Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc747tq-r1400b-tower4u-8xlff-red-psu-p-2394.html>