

Supermicro SuperChassis SC847BE1C-R1K28LPB 4U 36xLFF RED PSU

Kod producenta: CSE-847BE1C-R1K28LPB



Chassis Form Factor	Rack 4U
# of 3.5 hot-swap bays	36
Power Supply	Redundant
PSU Wattage	1280 W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-847BE1C-R1K28LPB • SuperChassis
847BE1C-R1K28LPB (Black)

Form Factor

4U chassis for motherboard support size of 13.68" x 13", 9.6" x 9.6"

Processor Support

Single and Dual Intel® and AMD processors

Dimensions

Height • 7" (178mm)
Width • 17.2" (437mm)
Depth • 27.5" (699mm)
Packaging • 27.2" (W) x 17.4"(H) 39.6" (L)
Gross Weight • 91 lb (41.28 kg)
Available Colors • Black

Expansion Slots

Up to Without Universal I/O (UIO) Card:
7 low-profile expansion slot(s)

Drive Bays

• 36x 3.5" hot-swap drive bay
Storage Chassis • SAS or enterprise SATA HDD only recommended

Backplane

HDD Backplane supports 36 SAS hard drives

Front Panel

Buttons

- Power On/Off button
- System Reset Button
- 2 Network Activity LEDs
- Fan Fail/System Over Heat LED

LEDs

- HDD activity LED
- Power Status LED
- Unit Identification (UID) LED

Motherboard (for CSE-847BE1C-R1K28LPB)

X10DRC-LN4+	X10DRC-T4+
X10DRH-C	X10DRH-CLN4
X10DRH-CT	X10DRH-I
X10DRH-iT	X10DRi
X10DRi-LN4+	X10DRi-T
X10DRi-T4+	X10SRH-CLN4F
X9DB3-F	X9DB3-TPF
X9DBi-F	X9DBi-TPF
X9DR3-F	X9DRD-7LN4F
X9DRD-7LN4F-JBOD	X9DRD-EF
X9DRH-7F	X9DRH-7TF
X9DRH-iF	X9DRH-iF-NV
X9DRH-iTF	X9DRi-F

System Cooling

Fans • 7x 8cm (7000 RPM) hot-swap PWM cooling fan

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)


Power Supply with Digital Switching Control & PMBus 1.2

1280W High-Efficiency (95%+) power supply

- 1000W Output @ 100-140V, 12-8A, 50-60Hz
- 1280W Output @ 180-240V, 8-6A, 50-60Hz

DC Output

- 1000W: +12V/83A; +5Vsb/4A
- 1280W: +12V/106.7A, +5Vsb/4A

Certification  **Platinum Certified**
[\[Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed, FCC
- Canada - CUL listed
- Germany - TUV Certified
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc847be1c-r1k28lpb-4u-36xlf-red-psu-p-2406.html>

