

Supermicro SuperChassis SC842XTQ-R606B 4U 5xLFF RED PSU

Kod producenta: CSE-842XTQ-R606B



Chassis Form Factor	Rack 4U
# of 3.5 hot-swap bays	5
Power Supply	Redundant
PSU Wattage	600 W
PSU Certification	80+ Platinum

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-842XTQ-R606B • SuperChassis 842XTQ-R606B (Black)

Form Factor

Industrial short-depth 4U rackmount chassis supports E-ATX, ATX and Micro-ATX motherboards; max. motherboard size 15.2" x 13.2"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 7.0" (178mm)
Width • 17.2" (437mm)
Depth • 20.5" (521mm)
Gross Weight • 46 lbs (20.9kg)
Available Colors • Black

Expansion Slots

11x Expansion slots total:
7x Full-height, Full-length + 4x Full-height, Half-length

Drive Bays

Hot-swap • 5x 3.5" SAS/SATA Hot-swap Drive Bays
• SAS or enterprise SATA HDD only recommended
Peripheral Bay(s) • 3x 5.25" Peripheral Drive Bays
• 1x Slim DVD-ROM Drive Bay

SAS / SATA Backplane

SAS / SATA Hard Drive Backplane

Front Panel

Buttons • Power On/Off Button
• System Reset Button
LEDs • Power LED
• Hard Drive Activity LED
• 2x Network Activity LEDs
• System Information LED
• Power Fail LED
Ports • 2x USB 2.0 Ports and 1x COM Port

Motherboard (for CSE-842XTQ-R606B)

[X9DRX+-F](#)

Server(s) for SC842XTQ-R606B

[6048R-TXR](#)

[6047R-TXRF](#)

System Cooling

Fans (Hot-plug) • 1x Front 9cm Intake Cooling Fan
• 2x Rear 8cm Exhaust Cooling Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply with Power Distributor

600W Redundant High-Efficiency Power Supplies w/Power Distributor, PMBus 1.2, P²C, and PFC
AC Input • 100-240V, 50-60Hz, 7.5-3.0A
DC Output • +5V standby: 3A
• +12V: 50A
With Power Distributor • +5V: 30 Amp
• +3.3V: 28 Amp
• -12V: 0.6 Amp



Certification

Platinum Certified
[\[Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc842xtq-r606b-4u-5x1ff-red-psu-p-2412.html>