

# Supermicro SuperChassis SC515-R407 1U 2xSFF RED PSU

Kod producenta: CSE-515-R407



Chassis Form Factor	Rack 1U
# of 2.5 fixed bays	2
Power Supply	Redundant
PSU Wattage	400 W
PSU Certification	80+ Platinum

*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

Product SKUs  
CSE-515-R407 • SuperChassis 515-R407 (No Paint)

Form Factor

Support STD and WIO MB

CPU Support

Single Intel® and AMD processors

Dimensions

**Height** 1.7" (43mm)  
**Width** 17.2" (437mm)  
**Depth** 16.9" (429mm)  
**Gross Weight** 18 lb (8.16 kg)  
Packaging 27" (W) x 8"(H) 24" (L)  
**Available Color** No Paint

Expansion Slots

Up to **Without Universal I/O (UIO) Card:**  
2 full height expansion slot(s)

Drive Bays

**Internal Bay** • Up to 2x 2.5" fixed with bracket

Front Panel

**Buttons**

- Power On/Off button
- System Reset Button
- 2 Network Activity LEDs
- Fan Fail/System Over Heat LED
- HDD activity LED
- Power Status LED

**LEDs**

Motherboard (for CSE-515-R407 )

[X10SDV-2C-7TP4F](#)      [X10SDV-4C-7TP4F](#)  
[X10SDV-7TP4F](#)      [X10SDV-7TP8F](#)  
[X10SRM-F](#)      [X10SRM-TF](#)

Server(s) for SC515-R407

[1018D-FRN8T](#)

System Cooling

**Fans** • 4x 40x56mm PWM fan  
• 2x fans for AOC cooling

Operating Environment (System)

Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)  
Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)  
Operating Relative Humidity Range • 8% ~ 90% (non-condensing)  
Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

AC/DC240V Input Redundant Power Supplies  
400W 1U Redundant Power Supplies with PMbus

Total Output Power • 400W

Dimension (W x H x L) • 54.5 x 40 x 220 mm

Input • 100 - 240Vac / 6.0 - 3.0A / 50-60Hz  
• 200 - 240Vdc / 3.4 - 3.2A (CCC Only)

+12V • Max: 33A / Min: 0.5A

+5V sb • Max: 3A / Min: 0A

Output Type • Gold Finger Connector Mating with Molex 45984-4343

Certification



**Platinum Level Certified**  
[\[ Test Report \]](#)

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC  
• Canada - CUL listed  
• Germany - TUV Certified  
• Europe/CE Mark  
• EN 60950/IEC 60950-Compliant

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc515-r407-1u-2xsff-red-psu-p-2459.html>