

Supermicro SuperChassis SC826BE1C-R920WB 2U 12xLFF RED PSU

Kod producenta: CSE-826BE1C-R920WB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	920 W
PSU Certification	80+ Platinum
Uwagi	Single Expander SAS3 12Gb/s Backplane

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-826BE1C-R920WB • SuperChassis
826BE1C-R920WB (Black)

Form Factor

2U chassis support for SMC Proprietary WIO motherboards; max. motherboard size - 12" x 13", 13" x 13.68"

* Support up to 12"x13" MB with rear 2.5" HDD option installed

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Width 17.2" (437mm)

Height 3.5" (89mm)

Depth 25.5" (648mm)

Gross Weight 52 lbs (23.6kg)

Packaging • 26.7" (W) x 11.4" (H) x 34.5" (L)

Available Colors Black

Expansion Slots

• WIO Slots (4x Full-height, Full-length + 3x Low-profile)

Drive Bays

Hot-swap 12x 3.5" Hot-swap SAS3/SATA Drive Bays and Optional 2x 2.5" Hot-swap SATA3 Drive Bays for OS mirroring
*SAS or enterprise SATA HDD only recommended

Backplane

SAS3 Single Expander Backplane features:

- Up to 12Gbps support
- In-band SES-2 Enclosure Management Support
- SAS3/SATA3 support
- 4x Mini-SAS HD connectors
- Scalability through cascading

Front Panel

Buttons • Power On/Off button
• System Reset button

System Cooling

Fans 3x 80mm 7K RPM Chassis middle fan w/ housing

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range • 10 - 35°C (50° - 95°F)

Non-Operating Temperature Range • -40 - 60°C (-40° - 140°F)

Humidity Range • 8 - 90% non-condensing

Non-Operating Humidity Range • 5 - 95% non-condensing

Power Supply with Power Distributor

920W high-efficiency (94+%) power supply with PMBus

AC Input • 100-240 V, 50-60 Hz, 11-4.4 Amp

DC Output • 4 Amp @ +5V standby
• 75 Amp @ +12V

With Power Distributor • +5V: 45 Amp
• +3.3V: 24 Amp
• -12V: 0.6 Amp

Certification



Platinum Certified

[[Test Report](#)]

Regulatory (Power Supply)

- Power Supply Safety / EMC**
- USA - UL listed
 - Canada - CUL listed
 - Germany - TUV Certified
 - EN 60950/IEC 60950-Compliant
 - CB Report
 - CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826be1c-r920wb-2u-12x1ff-red-psu-p-2462.html>
Copyright ©2024 www.superstorage.pl | czwartek, 21 listopad 2024 Strona: 2 / 3

