

# Supermicro SuperChassis SC825MTQ-R700LPB 2U 3xLFF RED PSU

Kod producenta: CSE-825MTQ-R700LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	3
Power Supply	Redundant
PSU Wattage	700W
Chassis Dimensions	437 x 89 x 450mm



*Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:*

## Product SKUs

CSE-825MTQ-R700LPB • SuperChassis 825MTQ-R700LPB (Black)

## Form Factor

2U chassis support for motherboard size - 12" x 13", 13.68" x 13" E-ATX

## Processor Support

Supports dual, single Intel® / AMD processors

## Dimensions

**Height** 3.5" (89mm)  
**Width** 17.2" (437mm)  
**Depth** 17.7" (450mm)  
**Gross Weight** 35 lbs (15.9kg)  
**Available Colors** Black

## Expansion Slots

• 7x low-profile expansion slots

## Drive Bays

**Hot-swap** 3x 3.5" SAS / SATA Hot-swap drive trays  
SAS or enterprise SATA HDD only recommended

## SAS / SATA Backplane

1x SAS / SATA backplane w/ Enclosure Management

## Peripheral Drives

**DVD-ROM** Slim DVD-ROM drive

## Front Panel

**Buttons**

- Power On/Off button
- System Reset button

**LEDs**

- Power LED
- Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED
- Power fail LED

**Ports** 2x USB Ports + DB9 COM Port

## Motherboard (for CSE-825MTQ-R700LPB )

<a href="#">X10SL7-F</a>	<a href="#">X10SLA-F</a>
<a href="#">X10SLH-F</a>	<a href="#">X10SLL+-F</a>
<a href="#">X10SLL-F</a>	<a href="#">X10SLM+-F</a>
<a href="#">X10SLM+-LN4F</a>	<a href="#">X10SLM-F</a>
<a href="#">X8DA3</a>	<a href="#">X8DA6</a>
<a href="#">X8DAE</a>	<a href="#">X8DAi</a>
<a href="#">X8DAL-3</a>	<a href="#">X8DAL-i</a>
<a href="#">X8DT3</a>	<a href="#">X8DT3-F</a>
<a href="#">X8DT3-LN4F</a>	<a href="#">X8DT6</a>
<a href="#">X8DT6-F</a>	<a href="#">X8DTE</a>
<a href="#">X8DTE-F</a>	<a href="#">X8DTH-6F</a>
<a href="#">X8DTH-i</a>	<a href="#">X8DTH-iF</a>
<a href="#">X8DTi</a>	<a href="#">X8DTi-F</a>
<a href="#">X8DTi-LN4F</a>	<a href="#">X8DTL-3</a>
<a href="#">X8DTL-3F</a>	<a href="#">X8DTL-6F</a>
<a href="#">X8DTL-I</a>	<a href="#">X8DTL-IF</a>
<a href="#">X8SI6-F</a>	<a href="#">X8SIE</a>
<a href="#">X8SIE-F</a>	<a href="#">X8SIL</a>
<a href="#">X8SIL-F</a>	<a href="#">X8ST3-F</a>

## System Cooling

**Fans** 4x 4cm Counter-rotating Fans

## Operating Environment (System)

**Operating Temperature** • 5°C ~ 35°C (41°F ~ 95°F)  
Range  
**Non-Operating Temperature** • -40°C ~ 60°C (-40°F ~ 140°F)  
Range  
**Operating Relative Humidity** • 8% ~ 90% (non-condensing)  
Range  
**Non-Operating Relative Humidity** • 5% - 95% (non-condensing)  
Range

## Power Supply

700W (1 + 1) Redundant AC-DC high-efficiency power supply w/ PFC  
**AC Voltage** • 100 - 240V, 60-50Hz, 10 - 4 Amp  
**+5V standby** • 4 Amp  
**+12V** • 57 Amp  
**With Power Distributor**

- +5V: 30 Amp
- +3.3V: 24 Amp
- -12V: 0.6 Amp

## Regulatory (Power Supply)

**Power Supply Safety / EMC**

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- CCC Certification

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc825mtq-r700lpb-2u-3x1ff-red-psu-p-2464.html>

Copyright ©2024 www.superstorage.pl | czwartek, 21 listopad 2024

Strona: 2 / 3

