

Supermicro SuperChassis SC733T-500B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-733T-500B



Chassis Form Factor	Mid-Tower
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Bronze

Product SKUs

CSE-733T-500B • SuperChassis 733T-500B (**Black**)

Form Factor

Mid-Tower & Workstation chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height • 16.8" (427 mm)
Width • 7" (178 mm)
Depth • 20.9" (531 mm)
Weight • 39 lbs (17.7 kg)
Available Colors • Black

Expansion Slots

7x Full-height, Full-length I/O expansion slots

Drive Bays

Hot-swap • 4x 3.5" SAS / SATA hot-swap drive bays
• SAS or enterprise SATA HDD only recommended
Peripheral Bay • 2x 5.25" peripheral drive bay
• 1x 3.5" bay

SATA Backplane

4 x 3.5" SATA Backplane

Front Panel

Buttons • Power On/Off button
• System Reset button
LEDs • Power LED
• Hard drive activity LED
• Network activity LED
• System Overheat LED
Ports • 2x Front side USB ports (USB 2.0 ready)

System Cooling

Fans • 1x 92mm Front Thermal Fan

Operating Environment (System)

Operating Temperature Range • 10° - 35°C (50° - 95°F)
Non-Operating Temperature Range • -40° - 70°C (-40° - 158°F)
Humidity Range • 8 - 90% non-condensing
Non-Operating Humidity Range • 5 - 95% non-condensing

Power Supply

500W AC power supply w/ PFC
AC Voltage • 100 - 240V, 50-60Hz, 7-3.5 Amp
+5V • 20 Amp
+5V standby • 3 Amp
+12V1 • 17 Amp
+12V2 • 17 Amp
+12V3 • 17 Amp
+12V4 • 18 Amp
-12V • 0.5 Amp
+3.3V • 15 Amp

Certification



Bronze Certified
[[Test Report](#)]

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• Germany - TUV Certified
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant
• CCC Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc733t-500b-mid-tower-4x1ff-fix-psu-p-2480.html>