

Supermicro MBD-X10SRA, Single SKT, Intel C612 Chipset, SATA, 2xGbE Bulk

Kod producenta: MBD-X10SRA-B



Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3 Intel Xeon E5-1600v3
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM DDR4 ECC UDIMM DDR4 non-ECC UDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	8
Max Memory Size	512 GB
# of PCIe x16 3.0	4
# of PCIe x4 2.0	2
# of USB Ports	6 x USB 3.0 (rear) 2 x USB 3.0 (header)
# of SATA Ports	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i210-AT Dual Port Gigabit Ethernet
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 4x PCI-E 3.0 x16 slots (runs at 16/16/NA/8 or 16/8/8/8) 2x PCI-E 2.0 x1 (in x4) slots

Product SKUs	Chassis (Optimized for X10SRA-F)
MBD-X10SRA-F -B	Mid/Mini Tower Chassis: - SC732D3-903B
Physical Stats	4U / Tower Chassis: - SC743TQ-1200B-SQ - SC745BTQ-R1K28B-SQ
Form Factor • ATX	- To support the new generation
Dimensions • 12" x 9.6", (30.5cm x 24.4cm)	Important Intel® Xeon® processor-based motherboards, Revision K chassis is recommended. Please talk to your sales representative for details.
Processor	
CPU	
Core / Cache	
Note	
Note	
System Memory	Expansion Slots
Memory Capacity	- 4x PCI-E 3.0 x16 slots (runs at 16/16/NA/8 or 16/8/8/8) - 2x PCI-E 2.0 x1 (in x4) slots
Memory Type	PCI-Express PCI-E slot #1 supports (x4) and slot #4 (x16) is disabled when Intel Core i7-5820K is installed
DIMM Sizes	
Memory Voltage	
Error Detection	
On-Board Devices	System BIOS
Chipset	BIOS Type - 128Mb SPI Flash EEPROM with AMI BIOS
SATA	- Plug and Play (PnP) - APM 1.2 - DMI 2.3 - PCI 2.3
Network Controllers	BIOS Features - ACPI 1.0 / 2.0 / 3.0 / 4.0 - USB Keyboard support - Hardware BIOS Virus protection - SMBIOS 2.7.1 - UEFI 2.3.1 - RTC (Real Time Clock) Wakeup
Audio	Management
Input / Output	Software - IPMI 2.0 with KVM support - SuperDoctor® 5 - SuperDoctor® III - Watch Dog - ACPI Power Management - Keyboard Wakeup from Soft-Off - CPU Fan auto-off in sleep mode - Power-on mode for AC power recovery
SATA	PC Health Monitoring
LAN	Voltage - +12V, +3.3V, +5V, 1.05 (PCH), 1.2V (VDIMM), 3.3V standby, Chassis intrusion header, Monitors CPU voltages, VBAT - Total of 5 fan headers supporting up to 5 fans - 5 fans with tachometer status monitoring
USB	FAN - Status monitor for speed control - Status monitor for on/off control - Low noise fan speed control - Pulse Width Modulated (PWM) fan connectors - Monitoring for CPU and chassis environment
Audio	Temperature - CPU thermal trip support - PC temperature sensing logic - Thermal Monitor 2 (TM2) support - PECI
Keyboard/Mouse	LED - CPU / System Overheat LED - Suspend static indicator LED
Serial Port / Header	Other Features - Chassis intrusion detection - Chassis intrusion header - Chipkill support - RoHS
TPM	
OS Compatibility	
• Please reference the OS Compatibility Chart for details	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-mbd-x10sra-single-skt-intel-c612-chipset-sata-2xgbe-bulk-p-2569.html>