


# Supermicro SuperChassis SC504-203B 1U 1xLFF FIX PSU

Kod producenta: CSE-504-203B



Chassis Form Factor	Rack 1U
# of 3.5 fixed bays	1
Power Supply	Fixed
PSU Wattage	200 W
PSU Certification	80+ Gold
Chassis Dimensions	249 x 43 x 437mm



Product SKUs	Motherboard (for CSE-504-203B )	
CSE-504-203B • SuperChassis 504-203B (Black)	<a href="#">A1SAI-2550F</a>	<a href="#">A1SAI-2750F</a>
Form Factor	<a href="#">A1SRI-2358F</a>	<a href="#">A1SRI-2558F</a>
9.8"-Depth Mini 1U chassis support for maximum motherboard size - 6.7" x 6.7"	<a href="#">A1SRI-2758F</a>	<a href="#">A2SAV</a>
Processor Support	<a href="#">A2SAV-L</a>	<a href="#">X10SBA</a>
Single Processor Support	<a href="#">X10SBA-L</a>	<a href="#">X10SDV-12C-TLN4F</a>
Dimensions	<a href="#">X10SDV-16C-TLN4F</a>	<a href="#">X10SDV-2C-7TP4F</a>
Height • 1.7" (43mm)	<a href="#">X10SDV-2C-TLN2F</a>	<a href="#">X10SDV-2C-TP4F</a>
Width • 17.2" (437mm) <<< Release form has 17.3"	<a href="#">X10SDV-2C-TP8F</a>	<a href="#">X10SDV-4C+-TLN4F</a>
Depth • 9.8" (249mm)	<a href="#">X10SDV-4C+-TP4F</a>	<a href="#">X10SDV-4C-7TP4F</a>
Packaging • 25.8" (W) x 6.1" (H) x 18.3" (L)	<a href="#">X10SDV-4C-TLN2F</a>	<a href="#">X10SDV-4C-TLN4F</a>
Gross Weight • 10 lbs (4.5kg)	<a href="#">X10SDV-6C+-TLN4F</a>	<a href="#">X10SDV-6C-TLN4F</a>
Available Colors • Black	<a href="#">X10SDV-7TP4F</a>	<a href="#">X10SDV-7TP8F</a>
Expansion Slots	<a href="#">X10SDV-8C+-LN2F</a>	<a href="#">X10SDV-8C-TLN4F</a>
• Up to 1x full-height, half-length PCI expansions slot*	<a href="#">X10SDV-F</a>	<a href="#">X10SDV-TLN4F</a>
*NOTE: Riser Card Required, See 'Drive Bays' for possible configurations	<a href="#">X10SDV-TP8F</a>	<a href="#">X10SLV-Q</a>
Drive Bays	<a href="#">X11SBA-F</a>	<a href="#">X11SBA-LN4F</a>
Internal Bay	<a href="#">X9SBA-F</a>	<a href="#">X9SCAA</a>
• 1x 3.5" Internal Drive Bay with 1x Half-height, Half-length PCI	<a href="#">X9SCAA-L</a>	<a href="#">X9SKV-1105</a>
• OR 2x 3.5" Internal Drive Bay	<a href="#">X9SKV-1125</a>	<a href="#">X9SKV-B915</a>
• OR 2x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI	<a href="#">X9SPV-F-3217UE</a>	<a href="#">X9SPV-F-3610ME</a>
• OR 4x 2.5" Internal Drive Bay	<a href="#">X9SPV-LN4F-3LE</a>	<a href="#">X9SPV-LN4F-3OE</a>
• Only SAS or enterprise SATA HDD recommended	<a href="#">X9SPV-M4</a>	<a href="#">X9SPV-M4-3OE</a>
Front Panel	<a href="#">X9SPV-M4-3UE</a>	
Buttons	Server(s) for SC504-203B	
LEDs	<a href="#">5017P-TLN4F</a>	<a href="#">5017P-TF</a>
I/O Ports	<a href="#">5018A-LTN4</a>	<a href="#">5018D-LN4T</a>
• Power On/Off button	<a href="#">5017A-EF</a>	<a href="#">5017A-EP</a>
• System Reset button	<a href="#">5017K-N6</a>	
• Power LED	Operating Environment (System)	
• Hard drive activity LED	Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)	
• 2x Network activity LEDs	Range	
• System Overheat LED	Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)	
• 1x VGA, IPMI, 4xLANs, 1x COM, 4xUSB, 1xKeyboard/Mouse	Range	
	Operating Relative Humidity • 8% ~ 90% (non-condensing)	
	Range	
	Non-Operating Relative Humidity • 5% - 95% (non-condensing)	
	Range	
	Power Supply	
	200W Low Noise AC-DC power supply with PFC	
	AC Voltage • 100 - 240V, 50-60Hz, 2.6 Amp Max	
	+5V • 8.0 Amp (max.)	
	+5V standby • 2.0 Amp (max.)	
	+12V • 16 Amp (max.)	
	-12V • 0.5 Amp (max.)	
	+3.3V • 8.0 Amp (max.)	
		
	Certification <b>Gold Certified</b>	
	Regulatory (Power Supply)	
	• USA - UL listed, FCC	
	• Canada - CUL listed	
	Power Supply • CCC Certification	
	Safety / EMC • EN 60950/IEC 60950-Compliant	
	• Europe/CE Mark	
	• Germany - TUV Certified	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc504-203b-1u-1x1ff-fix-psu-p-2662.html>