

Supermicro SuperChassis SC502-200B 1U 1xLFF FIX PSU

Kod producenta: CSE-502-200B



Chassis Form Factor Rack 1U

of 3.5 fixed bays 1

Power Supply Fixed

PSU Wattage 200W

PSU Certification 80+

Uwagi 200W High-Efficiency Low Noise Power Supply



Product SKUs



CSE-502-200B • SuperChassis 502-200B

Form Factor



• 9.8" Mini 1U chassis support for maximum motherboard size: Micro-ATX 9.6" x 9.6"

Processor Support



• Single 35W maximum Intel® Celeron® 400 series processors

Dimensions



Height - 1.7" (43 mm)
Width - 17.2" (437 mm)
Depth - 9.8" (249 mm)
Gross Weight - 10 lbs (4.54 kg)
Packaging (W x H x L) - 25.8" (655 mm) x 6.1" (155 mm) x 18.3" (465 mm)
Available Color - Black

Expansion Slots



- 1x full-height half-length PCI expansion slot (Optional) (Riser Card Required)

Drive Bays



- 1 x 3.5" fixed drive bay
- Optional 1 x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI
- Optional 2 x 2.5" Internal Drive
- SAS or enterprise SATA HDD only recommended

Front Panel



Buttons - Power On/Off button
- System Reset Button
- 2 Network Activity LEDs
LEDs - Fan Fail/System Over Heat LED
- HDD activity LED
- Power Status LED

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc502-200b-1u-1x1ff-fix-psu-p-2881.html>

Operating Environment (System)



Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range - -40°C - 60°C (-40°F - 140°F)
Operating Relative Humidity Range - 8% - 90% (non-condensing)
Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)

Power Supply

1U 200W Multi-output power supply with 80plus w/20pin output
Power Efficiency - 86%
Total Output Power and Input - 200W with Input 100 - 240Vac
AC Input Frequency - 50-60Hz
Dimensions (L x W x H) - 193 x 76 x 40 mm
Output Type - 20pin ATX
-12V - Max: 0.5A / Min: 0A
+12V - Max: 16A / Min: 0.2A (100Vac - 240Vac)
+5V - Max: 8AA / Min: 0.2A
+3.3V - Max: 8A / Min: 0.2A
+5Vsb - Max: 2A / Min: 0.2A
Certification - **Certified**

Regulatory (Power Supply)



Power Supply Safety / EMC - CCC
- CE/EMC
- FCC class B
- TUV/CB
- UL/CUL