

Supermicro SuperChassis SC823MTQ-R700LPB 2U 3xLFF RED PSU

Kod producenta: CSE-823MTQ-R700LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	3
Power Supply	Redundant
PSU Wattage	700W
Chassis Dimensions	437 x 89 x 450mm

Product SKUs	<input type="checkbox"/>	Motherboard (for CSE- 823MTQ-R700LPB)
<input type="checkbox"/>		
CSE-823MTQ-R700LPB • SuperChassis 823MTQ-R700LPB	<input type="checkbox"/>	
		X8DTH-6 X8DTH-6F
Form Factor		X8DTH-i X8DTH-iF
<input type="checkbox"/>		X8DT6 X8DT6-F
• 2U chassis supports for maximum motherboard sizes - E-ATX 12" x 13", ATX 12" x 10" motherboards		X8DTE X8DTE-F
		X8DT3 X8DT3-F
Processor Support		X8DTi X8DTi-F
<input type="checkbox"/>		X8DTi-LN4F X8DT3-LN4F
• Dual and Single Intel® and AMD processors		X8DTL-3 X8DTL-3F
		X8DTL-i X8DTL-iF
Dimensions		X8DTL-6F X8DTL-6L
<input type="checkbox"/>		X8DTL-L X8DA6
Height - 3.5" (89 mm)		X8DAE X8DA3
Width - 17.2" (437 mm)		X8DAi X8DAL-3
Depth - 17.7" (450 mm)		X8DAL-i X8STE
Gross Weight - 42 lbs (19.05 kg)		X8SIL X8SIL-F
Packaging (W x H x L) - 23.4" (594 mm) x 9.9" (251 mm) x 32.5" (826 mm)		X8SIE X8SIE-F
Available Color - Black		X11SSQ X11SSZ-TLN4F
		X11SSZ-F X11SSZ-QF
		X11SSQ-L
Expansion Slots		
<input type="checkbox"/>		
- 7 low-profile expansion slot(s)		Systems Cooling
Drive Bays		<input type="checkbox"/>
<input type="checkbox"/>		
- 3 x 3.5" hot-swap SAS/SATA drive bay with SGPIO		Fans - 4 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control
Backplane		Operating Environment (System)
<input type="checkbox"/>		<input type="checkbox"/>
- 3-port SC825M TQ (W/ AMI 9071) backplane, support up to 3x 3.5-inch SAS/SATA HDD		Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Peripheral Drives		Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
<input type="checkbox"/>		Operating Relative Humidity Range - 8% - 90% (non-condensing)
- 1 x slim DVD-ROM drive bay		Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)
- 2 x USB 2.0 ports		
- 1 x COM port tray		Power Supply
Front Panel		1U 700W hot swap redundant power supply.
<input type="checkbox"/>		Power Efficiency - 89%
Buttons - Power On/Off button		Total Output Power and Input - 700W with Input 100 - 240Vac
- System Reset Button		AC Input Frequency - 50-60Hz
- 2 Network Activity LEDs		Dimensions (L x W x H) - 346 x 76 x 40 mm
- HDD activity LED		Output Type - Backplanes (gold finger)
- Power Status LED		- Max: 58A / Min: 0.5A (100Vac - 240Vac)
- Power Fail LED		+5Vsb - Max: 4A / Min: 0A
- System Information LED		- PDB-PT823M-8824
		- O/P: 12V/75A
		Power Distributor - +5V Max: 30A
		- +3.3V Max: 24A
		- -12V Max: 0.6A
		Regulatory (Power Supply)
		<input type="checkbox"/>
		- BSMI
		- CCC
		Power Supply Safety / EMC - CE/EMC
		- FCC class A
		- TUV/CB
		- UL/CUL

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc823mtq-r700lpb-2u-3x1ff-red-psu-p-2882.html>