

Supermicro SuperChassis SC732D3-903B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-732D3-903B



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	900 W
PSU Certification	80+ Gold

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	<input type="checkbox"/>	Motherboard (for CSE- 732D3-903B)
<input type="checkbox"/>		<input type="checkbox"/>
CSE-732D3-903B • SuperChassis 732D3-903B		X10SRA-F
Form Factor		
<input type="checkbox"/>		
• Mid-tower chassis support motherboard sizes	<input type="checkbox"/>	Servers (for CSE- 732D3-903B)
E-ATX (12" x 13"), ATX (12" x 10") & Micro-ATX (9.6" x 9.6")	<input type="checkbox"/>	5038A-I
Processor Support		
<input type="checkbox"/>		
• Dual, single Intel® / AMD processors		
Dimensions		
<input type="checkbox"/>		
Height	- 16.7" (424 mm)	Fans
Width	- 7.6" (193 mm)	- 1 x 12cm rear exhaust fan(s)
Depth	- 20.68" (525 mm)	- Optional 1 x 12cm (front) cooling fan
Net Weight	- 27 lbs (12.25 kg)	
Gross Weight	- 30 lbs (13.61 kg)	Operating Environment (System)
Packaging (W x H x L)	- 11.97" (304 mm) x 21.38" (543 mm)	<input type="checkbox"/>
Available Color	- Black	Operating Temperature Range
		- 5°C - 35°C (41°F - 95°F)
		Non-Operating Temperature Range
		- -40°C - 70°C (-40°F - 158°F)
Expansion Slots		Operating Relative Humidity Range
<input type="checkbox"/>		- 8% - 90% (non-condensing)
- 7 full-height & full-length expansion slot(s)		Non-Operating Relative Humidity Range
Drive Bays		- 5% - 95% (non-condensing)
<input type="checkbox"/>		
- 4 x 3.5" fixed drive bay		Power Supply
- Optional 4 x 2.5" fixed drive bay		PS2/ATX 900W multiple outputs power supply, Gold level, 12cm fan
Peripheral Drives		Power Efficiency
<input type="checkbox"/>		- 90%
- 2 x standard 5.25" drive bay		Total Output
- 1 x card reader module		Power and Input
Front Panel		- 900W with Input 100 - 240Vac
<input type="checkbox"/>		AC Input Frequency
Buttons	- Power On/Off button	- 50-60Hz
LEDs	- 1 Network Activity LEDs	Dimensions (L x W x H)
	- HDD activity LED	- 190 x 150 x 86 mm
	- System Information LED	Output Type
Ports	- 2x USB 3.0 Port(s)	- 24pin ATX
	- 1x Audio Jack(s)	-12V
		- Max: 0.5A / Min: 0A
		- Max: 71.67A / Min: 0.4A
		- Max: 25A / Min: 0.1A (100Vac - 240Vac)
		- Max: 25A / Min: 0.1A (100Vac - 240Vac)
		+12V
		- Max: 25A / Min: 0.1A (100Vac - 120Vac)
		- Max: 25A / Min: 0.1A (100Vac - 240Vac)
		+5V
		- Max: 25A / Min: 0A
		+3.3V
		- Max: 25A / Min: 0A
		+5Vsb
		- Max: 4A / Min: 0.02A
		Certification
		- <input type="checkbox"/> Gold Certified
		Regulatory (Power Supply)
		<input type="checkbox"/>
		- BSMI
		- CCC
		Power Supply Safety / EMC
		- CE/EMC
		- FCC class B
		- TUV/CB
		- UL/CUL

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc732d3-903b-mid-tower-4xlf-fix-psu-p-3486.html>