

Supermicro SuperChassis SC113MFAC2-R608CB 1U 8xSFF RED PSU

Kod producenta: CSE-113MFAC2-R608CB



Chassis Form Factor	Rack 1U
# of 2.5 hot-swap bays	8
Power Supply	Redundant
PSU Wattage	600W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 507mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs	<input type="checkbox"/>	Motherboard (for CSE- 113MFAC2-R608CB)
<input type="checkbox"/>	<input type="checkbox"/>	X11DPL-i
CSE-113MFAC2-R608CB • SuperChassis 113MFAC2-R608CB		
Form Factor		
<input type="checkbox"/>	<input type="checkbox"/>	Servers (for CSE- 113MFAC2-R608CB)
• 1U Chassis, support motherboard size: ATX 12" x 10"		
Processor Support	<input type="checkbox"/>	1029P-MTR
<input type="checkbox"/>		
• Dual and Single Intel® and AMD processors		
Dimensions		Systems Cooling
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Height - 1.7" (43 mm)		Fans - 4 x 40x28mm PWM fan(s)
Width - 17.2" (437 mm)		- Optional 2 x fans for AOC cooling
Depth - 19.98" (507 mm)		
Gross Weight - 30 lbs (13.61 kg)		System Monitoring
Packaging (W x H x L) - 24" (610 mm) x 8.3" (211 mm) x 30" (762 mm)		<input type="checkbox"/>
Available Color - Black		- Chassis intrusion switch
Expansion Slots		Operating Environment (System)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- 1 full height expansion slot(s)		Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Drive Bays		Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
<input type="checkbox"/>		Operating Relative Humidity Range - 8% - 90% (non-condensing)
- 8 x 2.5" hot-swap SAS/SATA drive bay		Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)
Backplane		Power Supply
<input type="checkbox"/>		1U 600W redundancy PWS meet PMBus 1.2 with high efficiency and high power density
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices		Total Output Power and Input - 600W with Input 100 - 240Vac
Peripheral Drives		AC Input Frequency - 50-60Hz
<input type="checkbox"/>		Dimensions (L x W x H) - 220 x 54.5 x 40.25 mm
- Optional 1 x slim DVD-ROM drive bay		Output Type - Backplanes (gold finger)
Front Panel		+12V - Max: 50A (100Vac - 240Vac)
<input type="checkbox"/>		+5Vsb - Max: 3A
Buttons - Power On/Off button		- PDB-PT813M-2424
- System Reset Button		- O/P: 120/62
- 2 Network Activity LEDs		Power Distributor - +5V Max: 25
LEDs - HDD activity LED		- +3.3V Max: 25
- Power Status LED		- -12V Max: 0.6
- Unit Identification (UID) LED		Certification - 80 Plus Platinum (high-efficiency)
		Regulatory (Power Supply)
		<input type="checkbox"/>
		Power - BSMI
		Supply - CCC
		Safety / EMC - UL/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc113mfac2-r608cb-1u-8xsff-red-psu-p-3560.html>