

Supermicro SuperChassis SC213AC-R1K23LPB 2U 16xSFF RED PSU

Kod producenta: CSE-213AC-R1K23LPB



Chassis Form Factor	Rack 2U
# of 2.5 hot-swap bays	16
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Titanium
Chassis Dimensions	437 x 89 x 630mm

Product SKUs

CSE-213AC-R1K23LPB • SuperChassis 213AC-R1K23LPB

Motherboard (for CSE- 213AC-R1K23LPB)

[X11DPi-N](#) [X11DPi-NT](#)
[H11DSI-NT](#) [H11DSi](#)

Form Factor

• 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards

Servers (for CSE- 213AC-R1K23LPB)

Processor Support

• Dual and Single Intel® and AMD processors

[2029P-C1R](#) [2029P-C1RT](#)

Dimensions

Height - 3.5" (89 mm)
Width - 17.2" (437 mm)
Depth - 24.8" (630 mm)
Gross Weight - 60 lbs (27.22 kg)
Packaging (W x H x L) - 29" (737 mm) x 11" (279 mm) x 38.7" (983 mm)
Available Color - Black

Systems Cooling

Fans - 3 x 80mm heavy duty fan(s) with PWM fan(s) speed control

Expansion Slots

- 7 low-profile expansion slot(s)

Operating Environment (System)

Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range - 8% - 90% (non-condensing)
Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)

Drive Bays

- 16 x 2.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards
- 1 x 5.25" drive bay

Power Supply

1U 1200W/1000W Titanium Power Supply W/PMbus W76xL360xH40mm
Power Efficiency - 96%
Total Output Power and Input - 1000W with Input 100 - 127Vac
- 1200W with Input 200 - 240Vac
AC Input Frequency - 50-60Hz
Dimensions (L x W x H) - 336 x 76 x 40 mm
Output Type - Backplanes (gold finger)
- Max: 83A (100Vac - 127Vac)
+12V - Max: 100A (200Vac - 240Vac)
- Max: 100A (200 - 240)
+5Vsb - Max: 4A / Min: 0A
- PDB-PT216-8824
- O/P: 12V/100
Power Distributor - +5V Max: 30
- +3.3V Max: 24
- -12V Max: 0.6

Backplane

- 16-port 2U SAS3 12Gbps direct-attached backplane, support up to 16x 2.5-inch SAS3/SATA3 HDD/SSD

Certification - **Titanium Certified**

Peripheral Drives

- Optional 1 x slim DVD-ROM drive bay
- Optional 2 x USB 2.0 ports
- Optional 1 x COM port tray

Regulatory (Power Supply)

- BSMI
Power Supply Safety / EMC - CCC
- CE/EMC
- FCC class A
- UL/CB
- UL/CUL

Front Panel

Buttons - Power On/Off button
- System Reset Button
- 2 Network Activity LEDs
- HDD activity LED
LEDs - Power Status LED
- Power Fail LED
- System Information LED

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc213ac-r1k23lpb-2u-16xsff-red-psu-p-3731.html>