

ADAPTEC HBA 1100-8E SINGLE

Kod producenta: 2293300-R



Typ kontrolera	SAS/SATA HBA
Przepustowość	12Gb/s
Ilość kanałów zew.	8
maks. ilość urządzeń SAS	256
Złącza zew.	2x SFF-8644
Typ złącza magistrali	PCI Express 3.0 x8
Format	Low Profile
Waga	360g
Wyposażenie	Additional low profile vented bracket
Gwarancja	36 m-cy
Uwagi	Support for up to 256 SAS/SATA target devices (238 SSD/HDDs maximum support and remainder are reserved for expanders and enclosure management)

The 12 Gbps Adaptec HBA 1100-8e Host Bus Adapter has 8 external SAS/SATA ports in a x8 PCIe Gen 3 low-profile, MD2 form factor. Quality and reliability are assured through the unified hardened Smart Storage stack, now deployed to over 30 million servers. Built on the Microchip SmartIOC 2100 SAS/SATA protocol controller, HBA 1100-8e adapters can aggregate the performance of devices to the limits of the PCIe Gen 3 host bus at 6.6 Gbps, and achieve up to 1.5M IOPS without additional overhead or latency. The HBA 1100 adapters also have 40 percent power savings compared to previous generations, and significant power advantages versus competing solutions.

The HBA 1100, with its broad operating system support and ecosystem compatibility, is easy to implement and scale, and the unified maxView management tools and drivers across the Microchip HBA, RAID, and expander solutions enable easy manageability across the entire product line. HBA 1100 adapters are ideal solutions that support SAS/SATA HDDs, tape devices, and SSDs.

Product Features

- Quality and reliability through the unified, hardened Smart Storage stack, which is deployed in over 30 million servers
- 8 external native SAS/SATA ports in low-profile/ MD2 form factor
- +1.5M 4K random read IOPS; 40% lower power than previous generations
- 28 nm SmartIOC 2100 SAS/ SATA protocol controller
- Familiar GUI, CLI, and pre-boot tools ensures consistent performance and user experience across all products
- Proven compatibility with existing Adaptec Smart solutions, multiple operating systems, servers, enclosures, SSDs, HDDs, and LTO tape drives
- 12 Gbps SAS data rates using mini-SAS HD connectors

- CPU Platform Diversity -Support for Intel, AMD, and Cavium ThunderX2 (ARM)
- Open Source Management tools
 - Support for up to 256 SAS/SATA target devices (238 SSD/HDDs maximum support and remainder are reserved for expanders and enclosure management)
 - Multi-LUN support
 - SAS expander support
 - TLR
 - SATA NCQ
 - Hot plug drive support
 - S.M.A.R.T.
 - MPIO support
 - Multi-initiator (host)/clustering for SAS (HBA devices only)
 - Enclosure management: SES-2, SES-3; SFF-8485, SGPIO; SFF-8489, IBPI
 - BMC support
 - maxView Storage Manager
 - ARCCONF Command-line Interface
 - BIOS Configuration Utility (CTRL+A) Legacy Configuration Utility
 - ROM-Based uEFI BIOS Configuration Utilities
 - Microsoft Windows, Red Hat, SuSE, Debian, Oracle, CentOS, Ubuntu, VMware ESXi, FreeBSD, Solaris, Citrix Xen Server, and open-source Linux drivers
 - 2.535" H × 6.6" L (64 mm × 167 mm)
 - 50°C ambient and 55°C with 200 LFM airflow
 - CE, FCC, UL, C-tick, VCCI, KCC, CNS
 - RoHS
 - 3 years

Strona firmowa produktu: <https://www.superstorage.pl/adaptec-hba-1100-8e-single-p-4552.html>