

Supermicro SuperStorage SSG-631E-E1CR16L 3U DP 16xLFF 2x10 GbE IPMI RED PSU

Kod producenta: SSG-631E-E1CR16L



| | |
|------------------------|---|
| Category | Enterprise Server HPC, Data Center |
| Order option | Barebone |
| Chassis Form Factor | Rack 3U |
| CPU Socket | LGA 4677 (Socket E) |
| # of CPU sockets | 2 |
| Supported CPU's | Intel Xeon Scalable 5th Gen Intel Xeon Scalable 4th Gen |
| Max CPU TDP | 270 W |
| Chipset | Intel C741 |
| Memory Type | DDR5 ECC RDIMM |
| Memory Speed | 5600 MT/s 5200 MT/s 4800 MT/s 4400 MT/s 4000 MT/s |
| # of DIMM's | 16 |
| Max Memory Size | 4 TB |
| # of 2.5 hot-swap bays | 2 |
| # of 3.5 hot-swap bays | 16 |
| Backplanes | SAS3/SATA3 |
| # of USB Ports | 4 x USB 3.0 |
| Storage interface | Native SATA Optional SAS |
| Storage Controllers | Intel C741 |
| # of M.2 22110 | 2 |
| # of Serial Ports | 1 x Fast UART 16550 (rear) |
| # of 10GbE Ports | 2 x RJ45 |
| Network Controllers | Broadcom BCM57416 |
| Integrated BMC | IPMI Dedicated RJ45 |
| BMC chip | ASPEED AST2600 |
| TPM | 1 x TPM 2.0 10-pin Header |
| Power Supply | Redundant |
| PSU Wattage | 1200 W |
| PSU Certification | 80+ Titanium |
| Rack Rails | Included |
| Chassis Dimensions | 132 x 437 x 647 mm |
| Uwagi | 2 x PCIe 5.0 x8 FH slots 4 x PCIe 5.0 x16 FH slots |

UWAGA !!!

Oferowany produkt to platforma służąca do budowy swojej własnej konfiguracji (nie zawiera CPU, RAM czy HDD). Jeżeli potrzebujesz kupić gotowy system wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas systemów.

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superstorage-ssg-631e-e1cr16l-3u-dp-16x1ff-2x10-gbe-ipmi-red-psu-p-7261.html>