

# Supermicro SuperServer SYS-211TP-HPTRD 2U UP 4x(6xSFF 2x10GbE) IPMI RED PSU

Kod producenta: SYS-211TP-HPTRD



|                                   |   |
|-----------------------------------|---|
| Category                          | Multi-Access Edge Computing<br>Flex-RAN, Open-RAN vBBU  |
| Order option                      | Barebone  |
| Chassis Form Factor               | Rack 2U   |
| # of systems (nodes)              | 4   |
| CPU Socket                        | LGA 4677 (Socket E)   |
| # of CPU sockets                  | 1   |
| Supported CPU's                   | Intel Xeon Scalable 5th Gen<br>Intel Xeon Scalable 4th Gen                                    |
| Max CPU TDP                       | 270 W   |
| Chipset                           | C621A   |
| Memory Type                       | DDR4 ECC RDIMM<br>DDR4 ECC LRDIMM   |
| Memory Speed                      | 3200 MHz  |
| # of DIMM's (per node)            | 8   |
| Max Memory Size (per node)        | 2 TB  |
| Integrated GPU                    | ASPEED AST2600  |
| # of 2.5 hot-swap bays (per node) | 6   |
| # of PCIe x16 4.0 (per node)      | 2   |
| # of USB Ports                    | 2 x USB 3.2 Gen1  |
| Storage interface                 | Native SATA   |
| Storage Controllers               | Intel C621A   |
| # of M.2 22110 (per node)         | 2   |
| # of Serial Ports                 | 1 x Fast UART 16550 (header)  |
| # of 10GbE Ports (per node)       | 2 x SFP+  |
| # of 1GbE Ports (per node)        | 1 x RJ45  |
| Network Controllers               | Intel i210  |
| Integrated BMC                    | IPMI Dedicated RJ45   |
| BMC chip                          | ASPEED AST2600  |
| TPM                               | 1 x TPM 2.0 10-pin Header   |
| Power Supply                      | Redundant   |
| PSU Wattage                       | 2000 W  |
| PSU Certification                 | 80+ Titanium  |
| Rack Rails                        | Included  |
| Chassis Dimensions                | 88 x 438 x 730 mm   |
| Uwagi                             | PCI-Express Slots<br>Configuration:<br>1 x PCIe 5.0 x16 HHHH slot(s)<br>2 x PCIe 5.0 x16 FHHL |

## **UWAGA !!!**

*Oferowany produkt to platforma służąca do budowy swojej własnej konfiguracji ( nie zawiera CPU, RAM czy HDD ). Jeżeli potrzebujesz kupić gotowy system wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas systemów.*

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-211tp-hptrd-2u-up-4x6xsff-2x10gbe-ipmi-red-p-su-p-7485.html>